NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT,
SALEM, OREGON 97310
within 30 days from the date of well completion.

WATER WELL REPORT
STATE OF OREGON
(Please type or print)

(Do not write above this line)

MORR 1736

State Well No. 1S/27E-19ad

State Permit No.

(1) OWNER:
Name KEN TURNER
Address SAND HOLLOW HEPPNER ORE

(2) TYPE OF WORK (check):
New Well ☑ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☑ Driven ☐
Cable ☐ Jetted ☐
Bored ☐

(4) PROPOSED USE (check):
Domestic ☐ Industrial ☐ Municipal ☐
Irrigation ☑ Test Well ☐ Other ☐

(5) CASING INSTALLED: Threaded ☐ Welded ☑
12" Diam. from +2 ft. to 45 ft. Gage .250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS: Perforated? ☐ Yes ☑ No.
Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS: Well screen installed? ☐ Yes ☑ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? ☑ Yes ☐ No If yes, by whom? DRILLER
Yield: 2000 gal./min. with 23 ft. drawdown after 1 hrs.
" " " "
" " " "
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water 64 Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used PORTLAND CEMENT
Well sealed from land surface to 45 ft.
Diameter of well bore to bottom of seal 15 1/2 in.
Diameter of well bore below seal 12 1/4 TO 8 3/4 TO 710
Number of sacks of cement used in well seal sacks
How was cement grout placed? TREMIE

Was a drive shoe used? ☐ Yes ☑ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☑ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☑ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County MORROW Driller's well number
SE ¼ NE ¼ Section 19 T. 1S R. 27 E W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found 305 ft.
Static level 209 ft. below land surface. Date 12-31-79
Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 12 - 8 3/4
Depth drilled 710 ft. Depth of completed well 710 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
SAND	0	25	
GRAVEL	25	40	
BASALT Black	40	95	
" Black w-SS	95	305	
" RED	305	310	
" Black	310	710	

RECEIVED
APR 8 0 1980
WATER RESOURCES DEPT
SALEM, OREGON

Work started 12-10 1979 Completed 12-29 1979
Date well drilling machine moved off of well 12-31 1979

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Tony Bund (Drilling Machine Operator) Date 12-30, 1979
Drilling Machine Operator's License No. 544 933

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name Tony Bund well Drilling Inc (Person, firm or corporation) (Type or print)
Address Pendleton OR
[Signed] Tony Bund (Water Well Contractor)
Contractor's License No. 544 Date 12-30, 1979

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119