

NOTICE TO WATER WELL CONTRACTOR

The original and two copies
of this report are to be
filed with the

DEC 16 1968

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

RECEIVED

DEC 9 1968

State Well No.

35/25E-35cd

STATE ENGINEER, SALEM, OREGON 97210

within 30 days from date of well completion

STATE ENGINEER
SALEM, OREGONSTATE ENGINEER
SALEM, OREGON

Permit No.

(1) OWNER:

Name Albert Wright
Address Heppner Ore

(2) TYPE OF WORK (check):

New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary ☒ Driven ☐
Cable ☐ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):

Domestic ☐ Industrial ☐ Municipal ☐
Irrigation ☒ Test Well ☐ Other ☐

CASING INSTALLED:

Threaded ☐ Welded ☒

12" Diam. from 0 ft. to 26 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS:

Perforated? ☐ Yes ☒ No

Type of perforator used

Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? ☐ Yes ☒ No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WATER LEVEL: Completed well.

Static level 24 ft. below land surface Date
Artesian pressure lbs. per square inch Date

(9) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? ☒ Yes ☐ No If yes, by whom?

Yield: gal./min. with ft. drawdown after hrs.
500 GPM with 160 ft draw

Ball test gal./min. with ft. drawdown after 3 hrs.

Artesian flow g.p.m. Date

Temperature of water 56 Was a chemical analysis made? ☐ Yes ☐ No

(10) CONSTRUCTION:

Well seal—Material used Cement
Depth of seal 0-26 ft.
Diameter of well bore to bottom of seal 15 in.
Were any loose strata cemented off? ☐ Yes ☒ No Depth
Was a drive shoe used? ☐ Yes ☒ No
Did any strata contain unusable water? ☐ Yes ☒ No
Type of water depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☐ No Size of gravel:
Gravel placed from ft. to ft.

(11) LOCATION OF WELL:

County Morrow Driller's well number
SE 1/4 SW 1/4 Section 35 T. 35 R. 25E W.M.
Bearing and distance from section or subdivision corner

(12) WELL LOG:

Diameter of well below casing 12 to 175

Depth drilled 416 ft. Depth of completed well 416 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

MATERIAL	From	To	SWL
Top soil sandy brown	0	11	
Sand med gravel	11	17	
basalt hard black	17	95	
cc black med hard	95	150	
cc grey hard	150	344	
cc black green beans	344	363	
clay brown	363	382	
basalt black broken	382	395	
cc black clay beans	395	416	

Work started 7, 10 19 68 Completed 8, 15 19 68
Date well drilling machine moved off of well 19

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Arthur M. Zephyr Date 8, 15, 19 68
(Drilling Machine Operator)

Drilling Machine Operator's License No. 591

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME ROY T. FRENCH
(Person, firm or corporation) (Type or print)
Address Rte 2, Box 129 Pendleton Ore
[Signed] Roy T French
(Water Well Contractor)

Contractor's License No. 107 Date 8, 15, 19 68