WATER WELL REPORT STATE OF OREGON

RECEIVED APR 2 2 1981

WATER RESOURCES DEPT MOVER 246 SALEM, OREGON

State Permit No.

(1) OWNER:	(10) LOCATION OF WELL:
Name (arl William Thorpe	County W Wow Driller's well number
Address Rt	SW 4 SE 4 Section 2 T. 3.S. R. 26 E. W.M.
City debanes State Os 97836	Tax Lot # Lot Blk Subdivision
(2) TYPE OF WORK (check):	Address at well location:
New Well □ Deepening A Reconditioning A Abandon □	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found ft.
	Static level 27 ft. below land surface. Date 4-5-5
Rotary Air Driven	Artesian pressure lbs. per square inch. Date
□ Bored □ Thermal: Withdrawal □ Reinjection □	(12) WELL LOG: Diameter of well below casing
(5) CASING INSTALLED: Steel Plastic	Depth drilled 145 ft. Depth of completed well 725 ft.
Threaded	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry
Neve Diam from	for each change of formation. Report each change in position of Static Water Level
	and indicate principal water-bearing strata.
LINER INSTALLED:	MATERIAL From To SWL
ft. Gauge	Basalt, black / green Clayton 580 621
(6) PERFORATIONS: Perforated? ☐ Yes ☐ No	Basalt grey 621 685
Type of perforator used	Rock dark brown / blue Clayton 665 677 W.B.
Size of perforations in. by in.	Rock, med, Mackey green claystone 677 701
perforations from ft. to ft.	Rock, dark brown 1 green Clayton 701 725 W.B.
perforations from ft. to ft.	· 0
perforations from ft. to ft.	
(7) SCREENS: Well screen installed? □ Yes □ No	D. 1 Para (" 7 8"
Manufacturer's Name	Adamed from
Type Model No	from 180 to 639'
Diam. Slot Size Set from ft. to ft.	0
Diam. Slot Size Set from ft. to ft.	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Mulled 8" from 6391 to 125"
Was a pump test made? ☐ Yes 🛛 No If yes, by whom?	
d: gal./min. with ft. drawdown after hrs.	
"" " " " " " " " " " " " " " " " " " " "	
Air test 600 gal./min. with drill stem at 700 ft. 1 hrs.	.,
Bailer test gal/min. with ft. drawdown after hrs.	
Artesian flow g.p.m.	
perature of water Depth artesian flow encountered ft.	Work started 3-5 1981 Completed 4-6 1981
(9) CONSTRUCTION: Special standards: Yes \(\text{No} \)	Date well drilling machine moved off of well 45 198/
Well seal—Material used MM disturbel	Drilling Machine Operator's Certification:
Well sealed from land surface to	This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
Diameter of well bore to bottom of sealin.	[Signed] And I Date 4 18 , 198
Diameter of well bore below sealin.	(Drilling Machine Operator)
Number of sacks of cement used in well seal sacks How was cement grout placed?	Drilling Machine Operator's License No
now was cement grout piaceor	Water Well Contractor's Certification:
	This well was drilled under my jurisdiction and this report is true to
Was pump installed?	the best of my knowledge and belief.
Was a drive shoe used? ☐ Yes ☐ No Plugs Size: location ft.	Name TR9 GR/FF/M (Person, firm or corporation) (Type or print)
Did any strata contain unusable water? Yes No	Address 900 HERMISTON AVE, HERMISTON OR
Type of Water? depth of strata	Tank William
Method of sealing strata off	[Signed] (Water Well Contractor)
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	Contractor's License No 6.5 Date 4-7 , 1981
Gravel placed fromft.	