The original and first copy of this report are to be filed with the		35/26E-2
	/ WKN 490 /	
within 30 days from the date SEP2 6 19/5 (Do not write abo	ve this line) G-7262	
WATER RESOURCES DEPT.	(10) LOCATION OF WELL:	
(1) OWNER: SALEM, OREGON	County No 110 W Driller's well number 100	
Name Al. O.Smin		
Address Kf - / Brppall Ougan		
(a) TYPE OF WORK (sheek):	Bearing and distance from section or subdivision corner	
(2) TYPE OF WORK (check):	The state of the s	
New Well Deepening Reconditioning Abandon II If abandonment, describe material and procedure in Item 12.	(11) YVADED I EVET. Completed well	
	(11) WATER LEVEL: Completed well.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was the today	
Rotary Driven Domestic Dindustrial Municipal Domestic Dindustrial	Static level 30 ft. below land surface. Date 7/29/75	
Dug Bored I Irrigation Test Well Other	Artesian pressure lbs. per square inch. Date	
CASING INSTALLED: "Diam. fromft. toft. Gage	(12) WELL LOG: Diameter of well below casing S Depth drilled 223 ft. Depth of completed well 220 ft. Formation: Describe color, texture, grain size and structure of materials;	
ft. Gage	and show thickness and nature of each stratum	n and aquifer penetrated,
	with at least one entry for each change of format position of Static Water Level and indicate prince	ion. Report each change in cipal water-bearing strata.
PERFORATIONS: Perforated? Yes No.	MATERIAL	From To SWL
Type of perforator used		0 15
Size of perforations in. by in.	SAND I GIAVE	2 /2
perforations fromft. to	BOCK Block (Hard)	15 25
perforations fromft. toft.		
perforations from ft. to ft.	Rock Black (Med)	25 //5
(7) SCREENS: Well screen installed? Yes No		<u> </u>
Manufacturer's Name	Rock (Soft)	115 135 50
Type Model No.	Signal Control	138 150
Diam. Slot size Set from ft. to ft.	13801+ G/W	736 780
Diam. Slot sizeSet fromft, toft.	BASALT Black	150 160 50
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Volcania Rock (Soft)	160 200
Was a pump test made? ☐ Yes No If yes, by whom?	CO:CHIGHT ROSE POST	
Vield: 200 gal./min. with ft. drawdown after hrs.	Condomunte (Black)	200 215 10
is test pipe At 160"	284 - 1944 - 279 - 1971 - 1971 - 1981	
" " " " " " " " " " " " " " " " " " " "	ROCK BIN	215 220 20
Bailer test gal./min. with ft. drawdown after hrs.		
Artesian flow g.p.m.	7/.6 75	7/1675
Temperature of water Depth artesian flow encountered ft.	Work started 7/2 3 1975 Complete	-11
(9) CONSTRUCTION:	Date well drilling machine moved off of well Drilling Machine Operator's Certification:	
Well seal-Material used	This well was constructed under my	direct supervision.
Well sealed from land surface toft.	Materials used and information reported above are true to my best knowledge and belief	
Diameter of well bore to bottom of seal	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
Diameter of well bore below sealin. Number of sacks of cement used in well sealsacks	(Drilling Machine Operator)	
Number of sacks of cement used in well seal sacks Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No.	
Brand name of bentonite	Water Well Contractor's Certification:	
Number of pounds of bentonite per 100 gallons	· ·	
of water Ibs./100 gals.	The Manager of the state of the	
Was a drive shoe used? Yes No Plugs Size: location ft.	Name (Constitution of the State of the Stat	
Did any strata contain unusable water? Yes No	Register, firm or corporation) (Type or print)	
Type of water? depth of strata	Address Address	
Method of sealing strata off	[Signed] Water Well Con	bynator)
Was well gravel packed? Yes No Size of gravel:	1147	7/30 175
Gravel placed fromft. toft.	Contractor's License No. 7 Date	, 19
(USE ADDITIONAL S	HEETS IF NECESSARY)	SP*45658-119