

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON within 30 days from the date of well completion.

RECEIVED JUN 15 1970 STATE ENGINEER SALEM, OREGON

RECEIVED JUN 24 1970 STATE ENGINEER SALEM, OREGON

MORR 251

3/26-2

(1) OWNER:

Name CARL WILLIAM THORPE Address RT 1 HEPNER OREGON 97236

(2) TYPE OF WORK (check):

New Well [ ] Deepening [x] Reconditioning [ ] Abandon [ ] If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [ ] Driven [ ] Cable [x] Jetted [ ] Aug [ ] Bored [ ]

(4) PROPOSED USE (check):

Domestic [ ] Industrial [ ] Municipal [ ] Irrigation [x] Test Well [ ] Other [ ]

CASING INSTALLED:

Threaded [ ] Welded [ ] Diam. from ft. to ft. Gage

PERFORATIONS:

Perforated? [ ] Yes [x] No

Type of perforator used Size of perforations in. by in. perforations from ft. to ft.

(7) SCREENS:

Well screen installed? [ ] Yes [x] No

Manufacturer's Name Type Model No. Diam. Slot size Set from ft. to ft.

(8) WATER LEVEL: Completed well.

Static level Artesian ft. below land surface Date 4-14-70 Artesian pressure 2 PSI lbs. per square inch Date 4-14-70

(9) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? [x] Yes [ ] No If yes, by whom? OWNER Yield: 110 gal./min. with 257 ft. drawdown after 12 hrs.

Baller test 90 gal./min. with ft. drawdown after hrs. Artesian flow 12 g.p.m. Date 5-15-70 Temperature of water 54 Was a chemical analysis made? [ ] Yes [x] No

(10) CONSTRUCTION:

Well seal—Material used 3/4" casing or sealine wood Depth of seal done at this time ft. Diameter of well bore to bottom of seal in. Were any loose strata cemented off? [ ] Yes [x] No Depth Was a drive shoe used? [ ] Yes [ ] No Did any strata contain unusable water? [ ] Yes [ ] No Type of water depth of strata Method of sealing strata off Was well gravel packed? [ ] Yes [x] No Size of gravel: Gravel placed from ft. to ft.

(11) LOCATION OF WELL:

County MORROW Driller's well number 5 SW 1/4 SE 1/4 Section 2 T. 25 S. R. 26 E W.M. 1 Bearing and distance from section or subdivision corner 26 E 450' West 150' S of NE corner SW 1/4 - SE 1/4 4' dist 2 SW 1/4 of Sec 2-7-3-S-R 26 E County MORROW

(12) WELL LOG:

Diameter of well below casing 6 in.

Depth drilled 66 ft. Depth of completed well 500 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

Table with columns: MATERIAL, From, To, SWL. Entry: RESALT GREY HARD FINE GRAIN 434 500 AT

This work made me change in water production or artesian flow or pressure

Work started 4-14 1970 Completed 5-12 1970 Date well drilling machine moved off of well 5-15 1970

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] William C. Walter Date June 12, 1970 (Drilling Machine Operator)

Drilling Machine Operator's License No. 619

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME W.C. WALTER (Person, firm or corporation) (Type or print)

Address PO Box 251, Ione, Oregon

[Signed] William C. Walter (Water Well Contractor)

Contractor's License No. 508 Date 6-12 1970