WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310  (Please type	
	bove this line) State Permit No.
1) OWNER: SALEM, OREGON	(10) LOCATION OF WELL:
ame J. L. Osmin	County Morrow Driller's well number
Hupping, Ope at 97836	NW 1/4 SE 1/4 Section /2 T. 3 Q, R. 26 E, W.M.
2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner
Tew Well ☐ Deepening ☑ Reconditioning ☐ Abandon ☐ abandonment, describe material and procedure in Item 12.	
	(11) WATER LEVEL: Completed well.
3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found ft.
otary 😾 Driven 🛘 Domestic 🗎 Industrial 🗎 Municipal 🖂	Static level 36 ft. below land surface. Date 3-28-79
☐ Bored ☐ Irrigation ☐ Test Well ☐ Other ☐	Artesian pressure lbs. per square inch. Date
S) CASING INSTALLED: Threaded   Welded	(12) WELL LOG: Diameter of well below casing 8"
MtnC" Diam. from ft. to ft. Gage	
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials;
" Diam. from ft. toft. Gage	and show thickness and nature of each stratum and aquifer penetrated,
PERFORATIONS: Perforated?   Yes   No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
	MATERIAL From To SWL
ype of perforator used	
ize of perforations in. by in.	Basals, black Paren Claystone 226 218 W.B.
perforations fromft. toft.	Rock Insura 2011 306 3/6
perforations from ft. to ft	Basaer black 316 428
periorations from	Basalt, gray, 428 444
7) SCREENS: Well screen installed?   Yes   No	Basalt, brown green elayation 444 459
Manufacturer's Name	Basalr black 459 475
'ypeModel No	
Diam Slot size Set from ft. to ft.	Basaly, block 496 500
Diam. Slot size Set from ft. to ft.	
8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Vas a pump test made? ☐ Yes ☐ No If yes, by whom?	
d: gal./min. with ft. drawdown after hrs.	.
" " "	
AIRTEST \$00" 444 " 1"	
Sailer test 300 gal./min. with 344 ft. drawdown after hrs.	
esian flow g.p.m.	
perature of water Depth artesian flow encountered ft.	Work started 3-26 19 79 Completed 3-28 19 79
9) CONSTRUCTION:	Date well drilling machine moved off of well 3-28 1979
Vell seal-Material used NM disturbed	Drilling Machine Operator's Certification:
Vell sealed from land surface to ft.	This well was constructed under my direct supervision.
Diameter of well bore to bottom of seal in.	Materials used and information reported above are true to my best knowledge and belief.
Diameter of well bore below sealin.	[Signed] Monald Subject Date 3-28, 1979
Number of sacks of cement used in well sealsacks	(Drilling Machine Operator)
Now was cement grout placed?	Drilling Machine Operator's License No. 1210
	Water Well Contractor's Certification:
	This well was drilled under my jurisdiction and this report is
Was a drive shoe used? ☐ Yes ☐ No Plugs Size: location ft.	true to the best of my knowledge and belief.  Name TROY GRIFFIN
Did any strata contain unusable water? 🗌 Yes 🔲 No	(Person, firm or corporation) (Type or print)
'ype of water? depth of strata	Address 900 HER MISTON AVE HERMISTON ORE
Method of sealing strata off	[Signed] Troy Youffer.
Vas well gravel packed? ☐ Yes ☐ No Size of gravel;	(Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No. 65 Date 3-28 , 1979