

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

RECEIVED WATER WELL REPORT

WATER RESOURCES DEPARTMENT
SALEM, OREGON 97310
within 30 days from the date
of well completion

OCT 28 1977

STATE OF OREGON
(Please type or print)

MORR 263

State Well No. 35/210E-12db

State Permit No. G-8933

WATER RESOURCES DEPT.
SALEM, OREGON

(1) OWNER:
Name A. L. Osmin
Address Rt 1
Heppner, Oregon 97836

(2) TYPE OF WORK (check):
New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL: Rotary Driven
Cable Jetted
Dug Bored
(4) PROPOSED USE (check): Domestic Industrial Municipal
Irrigation Test Well Other

(6) CASING INSTALLED: Threaded Welded
8" Diam. from 0 ft. to 4.0 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(7) PERFORATIONS: Perforated? Yes No.
Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS: Well screen installed? Yes No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? Yes No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " "
" " " "
Ball-test 350 gal./min. with 140 ft. drawdown after 1 hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION: Well seal—Material used Cement
Well sealed from land surface to 40 ft.
Diameter of well bore to bottom of seal 11 in.
Diameter of well bore below seal 8 in.
Number of sacks of cement used in well seal 9 sacks
How was cement grout placed?

Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County Morrow Driller's well number
NW 1/4 & E 1/4 Section 12 T. 38. R. 26 E. W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found 90 ft.
Static level 25 ft. below land surface. Date 10-19-77
Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 8"
Depth drilled 226 ft. Depth of completed well 226 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

| MATERIAL | From | To | SWL |
|--------------------------------|------|-----|------|
| Topsoil | 0 | 21 | |
| Claystone & gravel | 21 | 25 | |
| Basalt, black | 25 | 90 | |
| Rock, black & green clay above | 90 | 226 | W.B. |

Work started 10-18 1977 Completed 10-19 1977
Date well drilling machine moved off of well 10-19 1977

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] John Van Swell Date 10-20, 1977
(Drilling Machine Operator)
Drilling Machine Operator's License No. 1027

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name TROY GRIFFIN
(Person, firm or corporation) (Type or print)
Address 900 HERMISTON AVE, HERMISTON ORE
[Signed] Troy Griffin
(Water Well Contractor)
Contractor's License No. 65 Date 10-20, 1977