NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

State Well No. State Permit No. ...

(1) OWNER:	(10) LOCATION OF WELL:			
Name JERRY MCELLIGOTT	County MORROW Driller's well number			
Address HEPPNER LEXINGTON HY	SE 45w 4 Section 12 T. 15 R. 24 F W.M.			
10Ne ORE	Bearing and distance from section or subdivis			
(2) TYPE OF WORK (check):			·	
New Well				
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed v	اآم		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	ven.		30 ft.
Rotary Driven Domestic C Industrial D Municipal D				
Di	Static level 6 ft. below land	surface. I	Date 3	<u>~27~61</u>
	Artesian pressure lbs. per squa	re inch. I		-
(5) CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well	1 - 1 1	15	2"
12 " Diam. from +1 ft. to -19 ft. Gage -250	Double desired 475			
Diam. from ft. to ft. Gage	To be a comp			<u>) ft.</u>
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and show thickness and nature of each stratu	ım and ad	uifer ne	netrated
(6) PERFORATIONS: Perforated? Ti Yes the No.	with at least one entry for each change of forms position of Static Water Level and indicate prin	ation. Repo	rt each c	hange in
(6) PERFORATIONS: Perforated? Yes No. Type of perforator used		1	er-bearin	g strata.
	MATERIAL	From	То	SWL
Size of perforations in. by in.	SOND	0	4	
perforations from ft. to ft.	Sano + Graver	<u>U</u>	12	
perforations fromft. toft.	Basalt Black GREY 155	12	130	
perforations from ft. to ft.	BLACH	130	140	
(7) SCREENS: Well screen installed? Yes No	11 DROWN - H20	148	148	
Manufacturer's Name	n Black		185	
Type Model No	" GREY		190	
Diam. Slot size Set from ft. to ft.	11 GREY-BR-H20	T	260	700
Diam. Slot size Set from ft. to ft.	u Black	+	464	
(8) WELL TESTS: Drawdown is amount water level is	" BLZCH		475	1000 T
AIR lowered below static level				
a pump test made? Thes I No If yes, by whom? DRILLER	CCCCVED			
Yield: 1000 + gal./min. with 180 ft. drawdown after / hrs.	Lt ba O ba i i i ba ka	ļ <u>.</u>		
" " "	DEC 3 1 1980	 		
<i>" " " " " " " " " "</i>	WATER RESOURCES DEPT			
er test gal./min. with ft. drawdown after hrs.	SALEM, OREGON	 		
arresian flow g.p.m.	- OFFICE OFF			
Temperature of water 58 Depth artesian flow encountered ft.	Work started 8-18 1980 Complete	. 0.0		1980
			-	
(9) CONSTRUCTION:	Date well drilling machine moved off of well	<u>8-1</u>	<u> 18</u>	19 <u>8</u> 0
Well seal-Material used PORTLEND ConeNT	Drilling Machine Operator's Certification:			
Well sealed from land surface toft.	This well was constructed under my Materials used and information reported	direct :	superv	rision.
Diameter of well bore to bottom of sealin.	best knowledge and belief	بيسر	· · · · · · · ·	
Diameter of well bore below seal	[Signed] (Drilling Machine Operator)	Date	12J,	1950
Number of sacks of cement used in well seal sacks How was cement grout placed? TREMIE	Drilling Machine Operator's License No.			
now was centent grout placed?	Diffing Intelline Operator's Intellise 140.	·	•	**********
	Water Well Contractor's Certification:			
	This well was drilled under my jurisdiction and this report is			
Was a drive shoe used? Yes No Plugs Size: location ft.	true to the best of my knowledge and belief			
Did any strata contain unusable water? Ves 440	Name Larry Burd Well Drillingerson, firm or corporation)	4		
Type of water? depth of strata	Address Pendleton Ove	- (Туре	e or print	J
Method of sealing strata off				•••••
Was well gravel packed? ☐ Yes Wo Size of gravel:	[Signed] day [Web Web Green		••••••	
Gravel placed from ft. to ft.	(Water Well Contra	' - '		~ -
II. II.	Contractor's License No.544 Date	ーくひ		19