

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM OREGON within 30 days from the date of well completion.

RECEIVED JUN 17 1969 STATE ENGINEER SALEM OREGON

WATER WELL REPORT

STATE OF OREGON JUL 28 1969

(Please type or print) (Do not write above this line)

RECEIVED MORR 412 STATE ENGINEER SALEM OREGON 6-4704

Well No. 1N/26-566a

Permit No.

(1) OWNER:

Name Grieb Farms, Inc. Address Star Rt. Lexington, Ore.

(2) TYPE OF WORK (check):

New Well [x] Deepening [] Reconditioning [] Abandon []

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [x] Driven [] Cable [] Jetted [] Dug [] Bored []

(4) PROPOSED USE (check):

Domestic [] Industrial [] Municipal [] Irrigation [x] Test Well [] Other []

CASING INSTALLED:

16" Diam. from 0 ft. to 100 ft. Gage 250. Threaded [] Welded [x]

PERFORATIONS:

Perforated? [] Yes [x] No. Type of perforator used. Size of perforations in. by in.

(7) SCREENS:

Well screen installed? [] Yes [x] No. Manufacturer's Name, Type, Model No., Diam., Slot size, Set from ft. to ft.

(8) WATER LEVEL: Completed well.

Static level 203 ft. below land surface Date 5/20/69. Man-pressure lbs. per square inch Date

(9) WELL TESTS:

Drawdown is amount water level is lowered below static level. Was a pump test made? [] Yes [x] No. Yield: 3060 gal./min. with 80 ft. drawdown after 17 hrs.

Bailer test gal./min. with ft. drawdown after hrs.

Artesian flow g.p.m. Date

Temperature of water Was a chemical analysis made? [] Yes [] No

(10) CONSTRUCTION:

Well seal—Material used Bentonite. Depth of seal 100 ft. Diameter of well bore to bottom of seal 20 in. Were any loose strata cemented off? [] Yes [x] No. Was a drive shoe used? [] Yes [x] No. Did any strata contain unusable water? [] Yes [x] No. Type of water? depth of strata. Method of sealing strata off. Was well gravel packed? [] Yes [x] No. Size of gravel: Gravel placed from ft. to ft.

(11) LOCATION OF WELL:

County Morrow Driller's well number #4 NW 1/4 NW 1/4 Section 5 T. 1 N R. 26 E W.M. Bearing and distance from section or subdivision corner 15 Ft. South and 1100 Ft East of NW corner sec. 5

(12) WELL LOG:

Diameter of well below casing 12" Depth drilled 1500 ft. Depth of completed well 1500 ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

Table with columns: MATERIAL, From, To, SWL. Rows include: TOP SOIL, BOULDERS, BLACK ROCK, BROWN CLAY, BLACK BASALT, GRAY BASALT, GREEN SHALE, BROKEN BASALT BLACK, HARD BASALT BLACK, FRACTURED BASALT BLACK, HARD BASALT BLACK, GRAY BASALT, FRACTURED BASALT BLACK, GRAY BASALT HARD, BROKEN BASALT BLACK, BROKEN BASALT WITH, STREAKED OF BROWN & Red Cinders, BLACK BASALT, GRAY BASALT, BROKEN BASALT BLACK, BLACK BASALT HARD.

Work started 12/15 1968 Completed 5/20 1969. Date well drilling machine moved off of well 5/25 1969

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Punctator Lewis Date 6/11 1969 (Drilling Machine Operator)

Drilling Machine Operator's License No. 341

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME Gary Grieb (Person, firm or corporation) (Type or print)

Address Star Rt. Lexington, Ore.

[Signed] Gary Grieb (Water Well Contractor)

Contractor's License No. 506 Date 6/12 1969

NOTICE TO WATER WELL CONTRACTOR:

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date of well completion.

RECEIVED
STATE OF OREGON
JUN 17 1969

RECEIVED
STATE OF OREGON
JUL 23 1969

Please type name of contractor
(Do not write above this line)

STATE ENGINEER
SALEM, OREGON

State Well No. 1N/26-566
Permit No. _____

(1) OWNER:

Name _____
Address _____

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Driven
Cable Jetted
Dug Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

CASING INSTALLED:

Threaded Welded

" Diam. from _____ ft. to _____ ft. Gage _____
" Diam. from _____ ft. to _____ ft. Gage _____
" Diam. from _____ ft. to _____ ft. Gage _____

PERFORATIONS:

Perforated? Yes No.

Type of perforator used _____
Size of perforations in. by _____ in.
_____ perforations from _____ ft. to _____ ft.
_____ perforations from _____ ft. to _____ ft.
_____ perforations from _____ ft. to _____ ft.
_____ perforations from _____ ft. to _____ ft.
_____ perforations from _____ ft. to _____ ft.

(7) SCREENS:

Well screen installed? Yes No

Manufacturer's Name _____
Type _____ Model No. _____
Diam. _____ Slot size _____ Set from _____ ft. to _____ ft.
Diam. _____ Slot size _____ Set from _____ ft. to _____ ft.

(8) WATER LEVEL: Completed well.

Static level _____ ft. below land surface Date _____
An pressure _____ lbs. per square inch Date _____

(9) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? Yes No If yes, by whom? _____
Yield: _____ gal./min. with _____ ft. drawdown after _____ hrs.
" " " " " "
" " " " " "
Bailer test _____ gal./min. with _____ ft. drawdown after _____ hrs.
Artesian flow _____ g.p.m. Date _____
Temperature of water _____ Was a chemical analysis made? Yes No

(10) CONSTRUCTION:

Well seal—Material used _____
Depth of seal _____ ft.
Diameter of well bore to bottom of seal _____ in.
Were any loose strata cemented off? Yes No Depth _____
Was a drive shoe used? Yes No
Did any strata contain unusable water? Yes No
Type of water? _____ depth of strata _____
Method of sealing strata off _____
Was well gravel packed? Yes No Size of gravel: _____
Gravel placed from _____ ft. to _____ ft.

(11) LOCATION OF WELL:

County _____ Driller's well number #4
_____ ¼ _____ ¼ Section T. R. W.M.
Bearing and distance from section or subdivision corner _____

(12) WELL LOG:

Diameter of well below casing _____

Depth drilled _____ ft. Depth of completed well _____ ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

MATERIAL	From	To	SWL
BROKEN BASALT BLACK	816	864	
BLACK BASALT HARD	864	877	
BROKEN BASALT BLACK	877	883	
GRAY BASALT HARD	883	889	
BROKEN BASALT BLACK	889	936	
BROKEN BASALT WITH STREAKED OF BROWN CINDERS	936	1056	
BROKEN BASALT BLACK	1056	1121	
BLACK BASALT HARD	1121	1138	
*POROUS BASALT BLACK	1136	1239	with B.
BLACK BASALT HARD	1239	1272	
POROUS BASALT BLACK	1272	1300	
GRAY BASALT HARD	1300	1314	
FRACTURED BASALT BLACK	1314	1336	
BLACK BASALT HARD	1336	1347	
FRACTURED BASALT BLACK	1347	1382	
GRAY BASALT HARD	1382	1438	
POROUS BASALT BLACK	1438	1486	
BLACK BASALT HARD	1486	1500	

Work started _____ 19 Completed _____ 19
Date well drilling machine moved off of well _____ 19

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] _____ Date _____, 19_____
(Drilling Machine Operator)

Drilling Machine Operator's License No. _____

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME _____
(Person, firm or corporation) (Type or print)

Address _____

[Signed] _____
(Water Well Contractor)

Contractor's License No. _____ Date _____, 19_____
(USE ADDITIONAL SHEETS IF NECESSARY)

Grieb Farms, Inc.

1N/26-5 bb
Morrow

Well was constructed with Mud Rotary. Do not believe much water encountered until 1136 Ft. Mud did thin down some, after 1136 Ft.

Lost circulation at 1272 Ft., took 30 bags Bentonite to get circulation back. Continued to hold circulation to 1500 Ft.

When rig was shut down for repair mud would go down between ~~to~~ 5' to 18'

RECEIVED
JUL 23 1969
STATE ENGINEER
SALEM OREGON