NOTICE TO WATER WELL CONTRACTOR
The original and first copy

of this report are to be

filed with the

WATER WELL REPORT
STATE OF OREGON
(Please type or print)

State Well No.

APR '7 = 1976
State Permit No.

STATE ENGINEER, SALEM, OREGON within 30 days from the date of well completion.

(Do not write above this line) WATER RESOURCES DEPT.

(1) OWNER:	(10) LOCATION OF WELL:
Name WILLIAM T POHERTY	County MORROW Driller's well number
Address LexING TON	NE % NE % Section /O T. IN R. 26 E W.M.
OR	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found See PREVIOUS ft.
Rotary Driven Domestic Industrial Municipal	Static level 207 ft. below land surface. Date 2-2776
Cable Dug Bored I Irrigation Test Well Other	7
EXISTING	Artesian pressure Ibs. per square inch. Date
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing 10"
" Diam. from ft. to ft. Gage	Depth drilled 376 ft. Depth of completed well 376 ft.
" Diam. fromft. to	Formation: Describe color, texture, grain size and structure of materials;
"Diam. from ft. to ft. Gage	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	OPEN WELL FROM 8"
perforations from	£ 218' 70 10" To 3 6
perforations fromft. toft.	
perforations from ft. to ft.	REAMED 10" EXISTING WELL
	TO STREIGHTEN FROM 45 50
(7) SCREENS: Well screen installed? Yes No	(07 112
Manufacturer's Name	174 179
Type Model No ft. to ft.	192 202
Diam. Slot size Set from ft. to ft.	DRILLING STEEDY BIK BARLT 218 300
	LERGE Hole (NO COTTINGS) 300 312 Ble Ch Basait 312 335
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Ble CH BASALT 3/2 335 BROWN SCORIA 335 350
Was a pump test made? ☐ Yes ☑ No If yes, by whom?	Black BASALT 350 360
d: gal./min. with ft. drawdown after hrs.	SOFTER BLOCK BASALT 360 375
" " "	Bleck BASA17 384 376
" " " "	
Bailer test gal./min. with ft. drawdown after hrs.	
Standard Garantin West 12. Grawdown arter ints.	
perature of water (8 Depth artesian flow encountered	Work started 2-25 1976 Completed 2-27 1976
	Date well drilling machine moved off of well 2-27 1976
(9) CONSTRUCTION:	
Well seal-Material used See Previous Loc	Drilling Machine Operator's Certification: This well was constructed under my direct supervision.
Well sealed from land surface toft.	Materials used and information reported above are true to my
Diameter of well bore to bottom of seal in. Diameter of well bore below seal in.	best knowledge and belief.
Number of sacks of cement used in well seal	[Signed] Jany Bund Date 2-27, 19.74
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No933
Brand name of bentonite	TV-4 VV-II C41 C121
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:
of water lbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was a drive shoe used? ☐ Yes ☐ No Plugs Size: location ft.	Name LERRY BURD WILL DRILLING
Did any strata contain unusable water?	(Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address Po Box 417 POLCTON
Method of sealing strata off	[Signed] Buy (Water Well Contractor)
Was well gravel packed? Yes No Size of gravel:	
Gravel placed from ft. to ft.	Contractor's License No. 544 Date 2.27 , 1976