STATE OF OREGON

WATER WELL REPORT (as required by ORS 537.765)

PLEASE TYPE or PRINT IMANK

985	11/1
ILS	DEPT Step

(1) OWNER:	(10) LOCATION OF WELL by legal description:
Name Rober Helbers DEPT	County
Address STER PAUTE SLEM, UREGON	Township (Township is North or South), Range (Range is East or West), WM.
City 10 We State OR	Tax Lot Lot Block Subdivision
(2) TYPE OF WORK (check):	MAILING ADDRESS OF WELL (or nearest address)
New Well ☐ Deepening ⚠ Reconditioning ☐ Abandon ☐	
If abandonment, describe material and procedure in Item 12.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL of COMPLETED WELL:
Rotary Air Driven Domestic Industrial Municipal	Depth at which water was first found 330 ft.
Thermal:	Static level 238 ft. below land surface. Date 8-8-8
Other:	Artesian pressure lbs. per square inch. Date
Coble Bored Piezometric Grounding Test	(12) WELL LOG: Diameter of well below casing
6) CASING INSTALLED: Steel Plastic	Depth drilled 2-70 ft. Depth of completed well 402 ft.
Threaded Welded	Formation: Describe color, texture, grain size and structure of materials; and show thickness
ft. to ft. Gauge	and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal
To Diam. from	water-bearing strata.
LINER INSTALLED: Steel Plastic Threaded Welded	MATERIAL From To SWL
1 mouded	BK SCORIA BASALT 130 145
6 Diam. from = 5 ft. to = 232ft. Gauge = 256	BL=CH 11 145 205
(6) PERFORATIONS: Perforated? ☐ Yes 🕩 No	BLECH SCORIB W/cby" 205 230
Size of perforations in. by in.	BL2 = 4 (1 230 270
perforations from ft. to ft.	BLECK BROKEN " 270 290
perforations from ft. to ft.	Black " 290 305
perforations from ft. to ft.	GRAV 9 305 330
	Black 4 27 " 330 350
(7) SCREENS: Well screen installed? Yes No	Week 9
Manufacturer's Name	BRN " 360 370
Type Model No	BL hr '1 320 380
Diam Slot Size Set from ft. to ft.	4. 24
Diam Slot Size Set from ft. to ft.	1724 4/57 " 386 400
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? Yes No If yes, by whom?	
eld: gal./min. with ft. drawdown after hrs.	
Air test 75 gal./min. with drill stem at 400 ft. / hrs.	
Bailer test gal./min. with ft. drawdown after hrs. Artesian flow g.p.m.	
mperature of water Depth artesian flow encounteredft.	
	Date work started 8-5-85 /completed 8-8-85
(9) CONSTRUCTION: Special standards: Yes \(\sigma \) No \(\frac{1}{2} \)	Date well drilling machine moved off of well 8-9-85 19
Well seal—Material used	(unbonded) Water Well Constructor Certification (if applicable):
Well sealed from land surface to ft.	This well was constructed under my direct supervision. Materials used and
Diameter of well bore to bottom of seal in.	information reported above are true to my best knowledge and belief.
Diameter of well bore below seal in.	[Signed]
Amount of sealing material sacks pounds	[Digited]
How was cement grout placed?	(bonded) Water Well Constructor Certification:
	Bond Issued by: (Surety Company Name)
m in had 4	On behalf of Lang Bund Well Drilling Long
Was pump installed?	(type or print name of Water Well Constructor)
Was a drive shoe used? ☐ Yes ☐ No Plugs Size: location ft. Did any strata contain unusable water? ☐ Yes ☐ No	This well was drilled under my jurisdiction and this report is true to the
Type of Water? depth of strata	best of my knowledge and belief:
	(Signed) Long Burd
Method of sealing strata off Was well gravel packed? Yes No Size of gravel:	(Water Well Constructor)
Was well gravel packed? I res Size of gravel	(Dated)
Graver placed from It. w It.	