NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

State Well No. 1N/26-35 Permit No.

STATE OF OREGON (Please type or pr (Do not write above the 6-5609

(1) OWNER: #2	(10) LOCATION OF WELL:		
(1) OWNER: Name Fritz Cutsforth Well #2	County Morrow Driller's well nu		
Address Heppner, Oregon	14 14 Section 35 T. 1 N	R. 26 E W.M.	
	Bearing and distance from section or subdivision	on corner	
(2) TYPE OF WORK (check):			
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found ft.		
(-)	1 18 72		
Cable Jetted			
Dug 🗌 Bored 🗋 Irrigation 📆 Test Well 🗍 Other 🗌	Artesian pressure lbs. per square inch. Date		
" CASING INSTALLED: Threaded □ Welded □	(12) WELL LOG: Diameter of well below casing		
" Diam. from ft. to ft. Gage	Depth drilled 508 ft. Depth of comple	_ 12#	
	Depth drifted 11. Depth of comp.		
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size a and show thickness and nature of each stratum		
	with at least one entry for each change of format position of Static Water Level and indicate prin-		
` PERFORATIONS: Perforated? ☐ Yes ☐ No.			
Type of perforator used	MATERIAL Discolar	From To SWL 238 272 67.5	
Size of perforations in. by in.	Basalt Black	272 351 64	
perforations from ft. to ft.	Grey Basalt Black Basalt	351 360 61	
perforations from ft. to ft.	Grey Basalt	360 384 59	
perforations from ft. to ft.	Black Basalt	384 392 58	
(7) SCREENS: Well screen installed? Yes No	Grey Basalt	392 440 54	
Manufacturer's Name	Shale very sticky black	1440 144 50.5	
Type Model No.	Grey Basalt	444 458 47	
Diam. Slot size Set from ft. to ft.	Green Soapstone	458 460 42.5	
Diam. Slot size Set from ft. to ft.	Grey Basalt	460 468 40	
	Mixed Rock & Soapstone	468 470 39	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Grey Basalt	470 484 27	
Was a pump test made? 🗆 Yes 🏝 No If yes, by whom?	Soft Basalt no cuttings	484 508 17'	
Yield: gal./min. with ft. drawdown after hrs.		<u> </u>	
. " " " "			
" " "			
Bailer test gal./min. with ft. drawdown after hrs.			
Artesian flow g.p.m.	Work started 11-23 19 ⁷¹ Complete	ed 1-19 19 72	
raperature of water Depth artesian flow encountered ft.		1-20 19 72	
(9) CONSTRUCTION:	Date well drilling machine moved off of well	19 12	
Well seal—Material used None	Drilling Machine Operator's Certification:		
Well sealed from land surface to ft.	This well was constructed under my Materials used and information reported		
Diameter of well bore to bottom of seal in.	best knowledge and belief		
Diameter of well bore below seal in.	[Signed] lead face y	Date 2 2 , 1975	
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No. 37		
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No.		
Brand name of bentonite	Water Well Contractor's Certification:		
Number of pounds of bentonite per 100 gallons		ction and this report is	
of water lbs./100 gals.			
Was a drive shoe used? ☐ Yes ☐ No Plugs Size: location ft.	1/Q11C		
Did any strata contain unusable water? Yes No	(Person, firm or corporation) P. O. Box 417 Pendle to	(Type or print) n. Oregon	
Type of water? depth of strata	Address		
Method of sealing strata off	[Signed] X Jany Bury	***************************************	
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	5) (Water Well Contr	actor) 72	
Gravel placed from ft. to ft.	Contractor's License No Date		