NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT RECEIVED MORR 44/

STATE OF OREGON

(Please type or print)

STATE ENGINEER Permit No. ... (Do not write above this line) SALEM. OREGON

DEC2 01973state Well No. 1 N

OWNER:	(10) LOCATION OF WELL:		
Name Burl Wattenburger Jr.	County MOTTOW Driller's well number		
Address Star Route Echo, Ore. 97826	34 34 Section 3 T. IN R. 27E W.M.		
(2) TYPE OF WORK (check):reamed from 8 to 10 in	Bearing and distance from section or subdivision from 154 to 255	on corner	
New Well Deepening Reconditioning Abandon Reconditioning Abandon			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found ft.		
Rotary Driven Domestic Industrial Municipal	Static level 60 ft. below land s	urface. Date I2-I4-7	
Cable		inch. Date	
CASING INSTALLED: Threaded Welded	A second of the second of t	elow casing	
"Diam. from ft. to ft. Gage ft. to ft. Gage ft. to ft. Gage			
Diam. from tt. to tt. Gage	Formation: Describe color, texture, grain size a		
Diam. from	and show thickness and nature of each stratum with at least one entry for each change of format		
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate princ		
Type of perforator used	MATERIAL	From To SWL	
		154 170	
	rock Ned.		
perforations from	rock med.		
perforations from ft. to ft.		210 235	
perforations from ft. to ft.	rock hard	234 255	
(7) SCREENS: Well screen installed? Yes No	-11 7 Jan 4 41 4 - 11		
	all I done to this well was r	eam it.	
? vfacturer's Name		·	
Type Model No			
Diam. Slot size Set from ft. to ft.			
Diam. Slot size Set from ft. to ft.			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level			
▼			
Was a pump test made? 🗋 Yes 📋 No If yes, by whom?			
'd: gal./min. with ft. drawdown after hrs.			
" "			
. # • #			
Bailer test none made gal./min. with ft. drawdown after hrs.			
Artesian flow g.p.m.	Work started I2-I2- 19 73 Complete	TO-T/1 (72	
perature of water Depth artesian flow encountered ft.	Work started I2-I2- 19 73 Complete Date well drilling machine moved off of well I		
(9) CONSTRUCTION:	L		
Well seal—Material usednone	Drilling Machine Operator's Certification:	direct curerists	
Well sealed from land surface toft.	This well was constructed under my Materials used and information reported		
Diameter of well bore to bottom of seal in.	best knowledge and belief	e eggen	
Diameter of well bore below sealin.	[Signed] I de College	Sate I 2-18, 19.73	
Number of sacks of cement used in well sealsacks	(Drilling Machine Operator) 300		
Number of sacks of bentonite used in well sealsacks	Drilling Machine Operator's License No.		
Brand name of bentonite	Western West Commenters Considerate	and the state of t	
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:		
of water lbs./100 gals.	This well was drilled under my jurisdiction and this report is		
Waī a drive shoe used? ☐ Yes 💆 No Plugs Size: location ft.	true to the best of my knowledge and belief.		
J ny strata contain unusable water? Yes No	Name (Person, firm or corporation) (Type or print)		
	AddresR . 2 Box 309-C Hermiston, Ore. 97838		
Type of water? depth of strata	18 6 000		
Method of sealing strata off	[Signed] (Water Well Control	octor)	
Was well gravel packed? Yes No Size of gravel:		2-18 ₁₉ 7	
TO TILLIAN TO THE TOTAL TO THE	COMMENCE DESCRIBE NO DAIP	IM " (