filed with the

STATE ENGINEER, SALEM, OREGON 9(310 within 30 days from the date of well completion.

NOTICE TO WATER WELL CONTRACTOR WORK WATER WELL REPORT CEIVED

STATE OF OREGON DEC 1 8 1975 State Well No. 11/22E-10
(Please type or print)

(Do not write above WATER RESOURCES DEPPermit No. .. SALEM OREGON

	Charles Charles
(1) OWNER:	(10) LOCATION OF WELL:
Name Leo AShBech	County MORROW Driller's well number 75-76
Address HERF ECHO ORC	Su: 4 SE 4 Section /O T. / N R. 27E W.
The state of the s	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	bearing and distance from section of subdivision corner
New Well ☐ Deepening	,
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found See Previous 66
Rotary Driven []	150
Cable	
Dug Bored I Irrigation II-Test Well Other I	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded □ Welded □	(12) WELL LOG: Diameter of well below casing 10 "
12 ft. Gage	17.5
"Diam from EXIST Note to ft. Gage ft. to ft. Gage	
	Formation: Describe color, texture, grain size and structure of material and show thickness and nature of each stratum and aquifer penetrate
7777777	with at least one entry for each change of formation. Report each change
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate principal water-bearing strain
ype of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	BASALT BLACK, HARD 225 238
perforations from ft. to ft.	" BLOCK HONEY COMB 238 280
perforations from ft. to ft.	" HARD 280 345
perforations from ft. to ft.	11 HONEY COMD 345 855
(7) SCREENS: Well screen installed? ☐ Yes ☐ No	" " HERD 355 400
Manufacturer's Name	
Type	10" 225 70 398
Diam. Slot size Set from ft. to ft.	6" 398 70 400
Diant, Slot size Set from 1t. to 1t.	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? Yes No If yes, by whom?	
Yield: gal./min. with ft. drawdown after hrs.	
" " "	- A #
" "	
Bailer test gal./min. with ft. drawdown after hrs.	
Artesian flow g.p.m.	
perature of water 68 Depth artesian flow encountered ft.	Work started 10 - 9 1975 Completed 10-10 197
(9) CONSTRUCTION:	Date well drilling machine moved off of well /0-13 192
Well seal—Material used EXISTING	Drilling Machine Operator's Certification:
Well sealed from land surface toft.	This well was constructed under my direct supervisio
Diameter of well bore to bottom of seal	Materials used and information reported above are true to n best knowledge and belief.
Diameter of well bore below sealin.	[Signed] Larry Burd Date 910 19
Number of sacks of cement used in well sealsacks	(Drilling Machine Operator)
Number of sacks of bentonite used in well sealsacks	Drilling Machine Operator's License No 9.33
Brand name of bentonite	
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:
of waterlbs./100 gals.	This well was drilled under my jurisdiction and this report true to the best of my knowledge and belief.
Was a drive shoe used? ☐ Yes ☐ No Plugs Size: location ft.	
Did any strata contain unusable water? Yes No	Name Larry Burd Willing (Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address POBOX 417 Pendleton or
Method of sealing strata off	reimail January
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	[Signed] Jany Bund (Water Well Contractor)
Gravel placed fromft. toft.	Contractor's License No. 5 44 Date 10 713