NOTICE TO WATER WELL CONTRACTOR

The original and first copy

of this report are to be

filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT GEIVED

STATE OF OREGON

(Please type or print)

(Do not write above this line)

(Please type or print)

(Do not write above this line)

MAR - \$197-State Well No

		/ 		, ecc	a
		クフト	17/	1	_
э.) N /	<u> </u>	<u>بر ا</u>	\mathcal{L}	_
	1		-	٠	DRE
	_ /		-		

(1) OWNER: OBSERVATION WELL	(10) LOCATION OF WELL:			
Name Vasper MYERS	County MORROW Driller's well number			
Address Echo ORC	SW 14 NF 1/4 Section 21 T. IN R.	2.7E W.M.		
	Bearing and distance from section or subdivision con	ner		
(2) TYPE OF WORK (check):				
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐				
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	650 ft.		
Potony It Driven Cl	801			
Cable	Static level 89 "ft. below land surface	Date L		
Dug Bored Irrigation Test Well Other	Artesian pressure lbs. per square inch			
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below	74 FO 450		
"Diam. from EXISTANC ft. Gage				
	Depth drilled 3/0 ft. Depth of completed t	vell 760 ft.		
	Formation: Describe color, texture, grain size and st and show thickness and nature of each stratum and			
	with at least one entry for each change of formation. I	Report each change in		
PERFORATIONS: Perforated? Yes D. No.	position of Static Water Level and indicate principal	water-bearing strata.		
Type of perforator used	MATERIAL From	m To SWL		
Size of perforations in. by in.	GREY BASALT 45	0 680 92#		
perforations from ft. to ft.	BLECK W/ GR CLZ7 ST. 65	0 690 1107		
perforations fromft. toft.	BLZCK BASALT 69	0 705		
perforations from ft. to ft.	11 11 W/CLST 70			
	1 1 72	5 750 280 7		
(7) SCREENS: Well screen installed? Yes Land	11 GREY 75	U 760		
Manufacturer's Name				
Type Model No				
Diam Slot size Set from ft. to ft.				
Diam Slot size Set from ft. to ft.				
(8) WELL TESTS: Drawdown is amount water level is				
lowered below static lever		 		
Was a pump test made? 🗌 Yes 🕩 No If yes, by whom?				
yield: gal./min. with ft. drawdown after hrs.				
" " "		 		
<u>n</u> n n n				
Bailer test gal./min. with ft. drawdown after hrs.				
Artesian flow g.p.m.				
erature of water 68 Depth artesian flow encountered ft.	Work started 2 - 7 197 7 Completed 2	2-9 1977		
	Date well drilling machine moved off of well			
(9) CONSTRUCTION:	Date wen drining machine moved out of wen	2-9 1977		
Well seal—Material used <u>Extistinal</u>	Drilling Machine Operator's Certification:			
Well sealed from land surface to ft.	This well was constructed under my dire Materials used and information reported above			
Diameter of well bore to bottom of seal in.	best knowledge and belief.			
Diameter of well bore below seal in.	[Signed] Jany Burn Date (Dryling Machine Operator)	2-7 19.77		
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No. 9.3	3 3		
Number of sacks of bentonite used in well seal sacks	Dining wathine Operator's incense No			
Brand name of bentonite	Water Well Contractor's Certification:	•		
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdiction and this report is			
of waterlbs./100 gals.	true to the best of my knowledge and belief.			
Was a drive shoe used? ☐ Yes ☐ No Plugs Size: location ft.	Name L2 RRY BURD WELL DRILLING (Person, firm or corporation) (Type or print)			
Did any strata contain unusable water? ☐ Yes ☐ No				
Type of water? depth of strata	Address 5543 SW: DOUGLES PENDLETON OR	<u> </u>		
Method of sealing strata off	[Signed] January 13 (Water Well Contractor)			
Was well gravel packed? Tyes ZNo Size of gravel:	1			
Gravel placed from ft. to ft.	Contractor's License No. 544 Date 2-	<u>7</u> 19 <i>7</i> 7		