

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

MORR 470

WATER WELL REPORT STATE OF OREGON (Please type or print)

RECEIVED

MAR 25 1976

(Do not write above this line)

State Well No. 14/27E-21 State Permit No.

WATER RESOURCES DEPT. SALEM, OREGON

(1) OWNER:

Name Gasper Myles Address Rt 2 Box 40 Heppner Oregon 97836

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandonment

(3) TYPE OF WELL:

Rotary Cable Driven Jetted Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal Irrigation Test Well Other

CASING INSTALLED:

Threaded Welded Diam. from ft. to ft. Gage

PERFORATIONS:

Perforated? Yes No

Type of perforator used Size of perforations in. by in. perforations from ft. to ft.

(7) SCREENS:

Well screen installed? Yes No

Manufacturer's Name Type Model No. Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? Yes No If yes, by whom? Yield: gal./min. with ft. drawdown after hrs. Baller test gal./min. with ft. drawdown after hrs. Artesian flow g.p.m. Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Not disturbed Well sealed from land surface to ft. Diameter of well bore to bottom of seal in. Diameter of well bore below seal in. Number of sacks of cement used in well seal sacks Number of sacks of bentonite used in well seal sacks Brand name of bentonite Number of pounds of bentonite per 100 gallons of water lbs./100 gals. Was a drive shoe used? Yes No Plugs Size: location ft. Did any strata contain unusable water? Yes No Type of water? depth of strata Method of sealing strata off Was well gravel packed? Yes No Size of gravel: Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Morrow Driller's well number SW 1/4 NE 1/4 Section 21 T. 17. R. 27E W.M. Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found ft. Static level 180 ft. below land surface. Date 3-17-76 Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 14" Depth drilled 0 ft. Depth of completed well 450 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with columns: MATERIAL, From, To, SWL. Contains handwritten entry: Enlarged well from 6" to 14" from 223' to 450'

Work started 2-27 1976 Completed 3-17 1976 Date well drilling machine moved off of well 3-17 1976

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] James T. Leitch Date 3-17, 1976 (Drilling Machine Operator)

Drilling Machine Operator's License No. 665

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name TROY GRIFFIN (Person, firm or corporation) (Type or print)

Address 900 HERMISTON AVE, HERMISTON ORE

[Signed] Troy Griffin (Water Well Contractor)

Contractor's License No. 65 Date 3-17, 1976