## WATER WELL REPORT STATE OF OREGON

MAR 20 1981

WATER RESOURCES DEPT SALEM, OREGON

MORR

State Well No. 1N 27E-23d

State Permit No.

(1) OWNER:	(10) LOCATION OF WELL:	
Name Bucking foll Ranch	County Wovrow Driller's well number	
Address Star L+	1W 4 SE 4 Section 23 T. 19, R. 27 E	, W.M.
City Echo, Oregon State 97826	Tax Lot # Lot Blk Subdivi	
(2) TYPE OF WORK (check):	Address at well location:	
New Well □ Deepening ★ Reconditioning □ Abandon □		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found ft.	
	Static level / 00 ft. below land surface. Date 3-4-8	
Rotary Mud	Artesian pressure lbs. per square inch. Date	
☐ Bored ☐ Thermal: Withdrawal ☐ Reinjection ☐	(12) WELL LOG: Diameter of well below casing /0"	
5) CASING INSTALLED: Steel Plastic	Depth drilled //O ft. Depth of completed well 3/0 ft.	
Threaded $\square$ Welded $\square$	Formation: Describe color, texture, grain size and structure of materials; and show	
Ningiam from ft. to ft. Gauge	thickness and nature of each stratum and aquifer penetrated, with at for each change of formation. Report each change in position of Stat	least one entry
"Diam. fromft. toft. Gauge	and indicate principal water-bearing strata.	
LINER INSTALLED:	MATERIAL From To	SWL
	Rock, med. black 200 21	
	Basaly 21/3	
(6) PERFORATIONS: Perforated? □ Yes □ No	- Busall 21/ 3/	
Type of perforator used		
Size of perforations in. by in.		
perforations from ft. to ft.		
perforations from ft. to ft.		<del></del>
perforations from ft. to. ft.		
(7) SCREENS: Well screen installed?   Yes   No		
Manufacturer's Name		
Type Model No.		
Diam. Slot Size Set from ft. to ft.		
Diam. Slot Size Set from ft. to ft.		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		
a pump test made?   Yes No If yes, by whom?		
d: gal./min. with ft. drawdown after hrs.		
" " "		<del></del>
Air test 500 gal./min. with drill stem at 300 ft. / hrs.		
Bailer test gal./min. with ft. drawdown after hrs.		
esian flow g.p.m.		
perature of water Depth artesian flow encountered ft.	Work started 3-3 1981 Completed 3-4	19 8/
(9) CONSTRUCTION: Special standards; Yes \( \sigma \) No \( \sigma \)	Work started 3-3 1987 Completed 3-47 Date well drilling machine moved off of well 3-47	19 8/
Well seal—Material used New disturbed		19 87
Well sealed from land surface toft.	Drilling Machine Operator's Certification:	
Diameter of well bore to bottom of sealin.	This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.	
Diameter of well bore below sealin.	[Signed] Lamb There 3-4 1981	
Number of sacks of cement used in well seal sacks	(Drilling Machine Operator)	
How was cement grout placed?	Drilling Machine Operator's License No	
0	Water Well Contractor's Certification:	
	This well was drilled under my jurisdiction and this report is true to	
Was pump installed?	the best of my knowledge and belief.	
Was a drive shoe used? ☐ Yes ☐ No Plugs Size: location ft.	Name TROY GRIFFIN	
Did any strata contain unusable water? ☐ Yes ☐ No	(Person, firm or corporation)  Address 900 HERMISTON AVE HERMISTON OR.	
Type of Water? depth of strata	nucless The Millian Control of the Millian Control	
Method of sealing strata off	[Signed] (Water Will Contractor)	
Was well gravel packed? ☐ Yes ☐ No Size of gravel:		, 19.87
Graval placed from 6t to 6t	Contractor's License No. Date 5-4	, 19 <i>.</i> 9.%.