NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT GETVED

STATE OF OREGON APR 111977 State Week No. 1

(Please type or print)
(Do not write above this has) SALEM. OREGON 6-4484

(1) UWNER: WILLIAM V. MCALI	County MORROW Driller's well:	number		
Address HEPPNER ORC	1	***	E	****
Address HeppNer ORE	S& 14 NW 14 Section 16 T. IN			<u>W.M.</u>
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivi	ilon corne	r	
New Well Deepening Reconditioning Abandon				
If abandonment, describe material and procedure in Item 12.				
	(11) WATER LEVEL: Completed	well.	5/16	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found		545	<u></u>
Rotary Driven Domestic Industrial Municipal Cable Jetted	Static level /4/5 ft. below land	surface.	Date 4-	<u>6-77</u>
Dug □ Bored □ Irrigation Test Well □ Other □	Artesian pressure lbs. per squa	are inch.	Date	•
CASING INSTALLED: Threaded Welded 5 2 4Diam. from 12 NS.71 NG. ft. Gage 250 "Diam. from ft. to ft. Gage "Diam. from ft. to ft. Gage	(12) WELL LOG: Diameter of well Depth drilled 325 ft. Depth of compound in the compoundation: Describe color, texture, grain size and show thickness and nature of each strat with at least one entry for each change of form	and structum and a ation. Rep	ture of a quifer peopre each	materials; enetrated, change in
PERFORATIONS: Perforated? Yes Yes Yes Yes Perforated? Yes Yes	position of Static Water Level and indicate pr	incipal wa	ter-beari	ng strata.
e of perforator used	MATERIAL	From	To	SWL
Size of perforations in. by in.	BASALT BLBCK	250	170	153
perforations from	" Bleck w/DROWN	270	443	
perforations from ft. to ft.	4 " w S/S	443	455	
perforations from ft. to ft.	4 Blach	453	0 45	
(7) SCREENS: Well screen installed? Yes No	" Rep	545	5 62	
Manufacturer's Name	4 Black w PE PYRITE		562	1000
Type Model No.	11 GREY	562	5 75	145
Diam. Slot size Set from ft. to ft.		+		
Diam. Slot size Set from ft. to ft.		1		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level Was a pump test made? Yes No If yes, by whom? Yold: gal./min. with ft. drawdown after hrs.				
, , , , , , , , , , , , , , , , , , , ,		1		
<u>" " "</u>		1		
Bailer test gal./min. with ft. drawdown after hrs.		1		
Artesian flow g.p.m.				
rerature of water 68 Depth artesian flow encountered ft.	Work started 3 - 25 1977 Comple	ted \$	- 4	10 75
CONSTRUCTION:	Date well drilling machine moved off of well	4	- 4	19 77
Well seal—Material used £XIS7/D6	Drilling Machine Operator's Certification			
Well sealed from land surface to ft.	This well was constructed under my Materials used and information reported			
Diameter of well bore to bottom of seal in.	best knowledge and belief.			~ 403
Diameter of well bore below seal in.	[Signed] Lany Bur	Date	<u> 1-4</u>	, 1972
Number of sacks of cement used in well seal sacks	(Drilling Machine Operator) Drilling Machine Operator's License No.	93	3	
How was cement grout placed?	Drining Machine Operator's License No.	<i>-</i>		
	Water Well Contractor's Certification:		÷	
	This well was drilled under my jurisc true to the best of my knowledge and be		nd this r	eport is
Was a drive shoe used? 🗌 Yes 🗎 No Plugs Size: location ft.	Name Farry Burd Well	Dail	10 in	
Did any strata contain unusable water? Yes	(Dirson, firm or corporation)		pe or win	
Type of water? depth of strata	Address 5543 5.42 Dong	Cas F	2a	Perdle
Method of sealing strata off	[Signed] Ley Bud			
Was well gravel packed? Yes No Size of gravel:	(Water Well Con	tractor)	•	
Gravel placed from ft. to ft.	Contractor's License No. 544 Date	4~	4	, 19.2.7
	ra vast e la comunicación de la			