NOTICE TO WATER WELL CONTRACTOR

The original and first copy

of this report are to be

filed with the

WATER WELL REPORT

State Well No. $2n/23\xi$ 8bc

Gravel placed from ft. to

filed with the

STATE OF OREGON
STATE ENGINEER, SALEM, OREGON 97310 FC E Pras Pipe or print) MORK 495
within 30 days from the date

53 pt of \$ 10.77	ove this line)			=
(1) OWNER: Name DAVID Che WATER DESOURCES DEP	T(10) LOCATION OF WELL:	S.		. **,**;
NATER PESOURCES DELL	County MORROW Driller's well nu	ımber		
	SW 14 N Att Section 8 T. 2N		F	W.M.
Address 10NC ORE		- T -		
	Bearing and distance from section or subdivisi	on corner	r	100 A 7 F. 1
(2) TYPE OF WORK (check):				, - 1, - 1 ,
New Well				
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell.		*
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(1) No. (1) 전 (1	25-	60	ft.
	id .			
Coble D Tetted D Municipal Domestic Municipal	Static level ft. below land s	uriace.	Date	2
Dug ☐ Bored ☐ Irrigation Test Well ☐ Other ☐	Artesian pressure Ibs. per squar	e inch.	Date	<u> </u>
CACING INCMALLED.				12/4
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well		ang	
12 " Diam. from +2 ft. to -135 ft. Gage 1958	Depth drilled 199 ft. Depth of compl	eted well	1 199	ft.
	Formation: Describe color, texture, grain size	and struc	ture of r	naterials;
	and show thickness and nature of each stratu	m and ac	quifer pe	netrated,
DEDECE A MICANG	with at least one entry for each change of forma position of Static Water Level and indicate prin	tion. Rep	ori each ter-beari	ng strata.
PERFORATIONS: Perforated? Yes No.		T	·	
Type of perforator used	MATERIAL	From	To	SWL
Size of perforations 1/2 in. by 8 in.	<u> </u>	0	15	
364 perforations from 20 ft. to 134 ft.	GREVEL	17	25	
perforations fromft. toft.	GREVEL	25	50	1006
	CLZY	50	92	
perforations from ft. to ft.	CLOY + GRAVEL	92	110	
(7) SCREENS: Well screen installed? ☐ Yes ☐ No	CLEY	110	118	
Manufacturer's Name	GLEX GRAVEL	118	125	
Type Model No.	Clay	125	137	
Piam. Slot size Set from ft. to ft.	100	132	199	
Sion Size Set from ft. to ft.	1888 ALT W/5-5	111	1000	
Jiam. Slot size Set from It. to		1		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		+		
A182		1	 	
Was a sump test made? Yes No If yes, by whom? DRILLER		+		
d: 100 gal./min. with 30 ft. drawdown after / hrs.	The second secon	+	-	
" " "				
		-		
" " " " " " " " " " " " " " " " " " " "		 	 	
Bailer test gal./min. with ft. drawdown after hrs.			_	
Artesian flow g.p.m.		<u> </u>	<u> </u>	
perature of water 56 Depth artesian flow encountered ft.	Work started 5-25 1978 Comple	ted 5	- 31	1977
	Date well drilling machine moved off of well	5	-31-	1977
(9) CONSTRUCTION:		<u>*</u>		
Well seal-Material used PARTLEUD COMENT	Drilling Machine Operator's Certification			
Well sealed from land surface toft.	This well was constructed under my Materials used and information reported	direc	t supe are tru	rvision. e to mv
Diameter of well bore to bottom of sealin.	best knowledge and belief.	. above		
Diameter of well bore below sealin.	[Signed] Jany Burd	Date	6-6	, 19.7
	(Deilling Machine Operator)			
Number of sacks of cement used in well sealsacks	Drilling Machine Operator's License No.	4	11	
Number of sacks of bentonite used in well seal sacks				
Brand name of bentonite	Water Well Contractor's Certification:			
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisc	liction a	nd this	report is
of water lbs./100 gals.	true to the best of my knowledge and be	lief.	<i>n</i> .	:
Was a drive shoe used? Yes No Plugs Size: location ft.	Name damy Bund Well	Pril	hores	
Did any strata contain unusable water? 🗌 Yes 🗗 No	(Verson, firm or corporation)	<i>1</i> 1 '	Type or pr	int)
Type of water? depth of strata	Address 5543 5 w Doug	Kan	12	
	A . A	rock	acon	
Method of sealing strata off	[Signed] (Water Well Con	tractor)		
Was well gravel packed? Yes I No Size of gravel:		6-	6	.27
Gravel placed from ft. to ft.	Contractor's License No. 3.4.4 Date		<u>ب</u>	, 19