TICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

Method of sealing strata off

Gravel placed from

Was well gravel packed? [] Yes No

WATER WELL REPORT

STATE	OF	OREGO	N	
IP eas	Уr	or plint)	ED	60

State Well No. Zn	/236-17ad
Diase were real real	•

State Well	NoLA	/23Ep-	17 aa
D1410 11 5		F	

WATER RESOURCES DEPARTMENT, STATE OF	oregon (3	State Well No.			
SALEM, OREGON 97310 within 30 days from the date of well completion. (Do not write an	ove this line)	State Permit No)	***************************************	
	4 1977				
(1) OWNED.	(10) LOCATION OF W	ELL:			
Name DAULD CHENCY WATER RESU	DURCES PERFOLD	Driller's well nu	mber		
Address 10 Ne ORP SALEM.	OREGON NE 14 Section	17 T. 210	R. 23	うた	W.M.
, (d. 655)	Bearing and distance from sec	tion or subdivision	on corne	r	
(2) TYPE OF WORK (check):		70			
New Well (Deepening (Reconditioning (Abandon	·	-7			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL:	Completed w	ell.		
	` '	_	D 11.		f+
n to the Dulman D	Depth at which water was firs			D.4. 6	-1-77
Rotary Driven Domestic Industrial Municipal Cable Jetted	Static level 120	ft. below land s			- (2)
Dug 🗌 Bored 🗍 Irrigation 🗎 Test Well 🗍 Other 📋	Artesian pressure	lbs. per squar	e inch.		11 #0 GO
CASING INSTALLED: Threaded □ Welded □	(19) WELL LOC.		_	• .	•
-		iameter of well b			
" Diam. from XIS7tl to Gage ft. Gage ft. Gage		Depth of compl			<u>.v.</u>
" Diam. fromft. toft. Gage	Formation: Describe color, ter and show thickness and natur	xture, grain size a	and struc	ture of n	naterials;
" Diam, from It. to It. dage	with at least one entry for each	n change of forma	tion. Rep	ort each o	change in
Perforated? Yes Avo.	position of Static Water Level	and indicate prin	cipal wa	ter-bearin	ıg strata.
ype of perforator used	MATERIAL		From	То	swL
Size of perforations in. by in.	BASALT BL	ock	480	490	
perforations from ft. to ft.	11 Block 4		490	495	
perforations from ft. to ft.	h BL	ech	495		
	1 Black +		515	535	
perforations from ft. to ft.	n BROWN		535	540	
(7) SCREENS: Well screen installed? Yes No	4 Bleck		540	618	
Manufacturer's Name	n Black + R	D4 35	618	630	
Type	" Block		630	663	
Diam. Slot size Set from ft. to ft.	A BLOCK & BRO	W N + 55	463	685	
Diam, Slot size Set from ft. to ft.					
			<u></u>		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level					
Was a pump test made? WYes \(\subseteq No \) If yes, by whom? DRILLER					
vied: 500 6 gal./min. with 400 ft. drawdown after / hrs.			<u> </u>		ļ
		:		ļ	<u></u>
OSTIMATE " " "		e;	<u> </u>	ļ	
, , , , , , , , , , , , , , , , , , , ,				ļ,	
Bailer test gal./min. with ft. drawdown after hrs.		-			
Artesian flow g.p.m.			<u> </u>		
rature of water 20 Depth artesian flow encountered ft.	Work started 6-1	19 77 Complet	ed 🗜	5-4	19 77
(A) CONCERNITY CONT	Date well drilling machine me	oved off of well		6-4	19 77
(9) CONSTRUCTION:	D. Illian Marking Operator	-'s Coutification			
Well seal—Material used FX157/V6	This well was constru	a 1984		t suner	rvision.
Well sealed from land surface to ft.	Materials used and inform	nation reported	above	are tru	e to my
Diameter of well bore to bottom of sealin.	best knowledge and belief.	_		_	
Diameter of well bore below seal in.	[Signed] (Drilling Mach	ine Operator)	Date	G 6	, 1977.
Number of sacks of cement used in well seal sacks	Drilling Machine Operator		93	3	
How was cement grout placed?	Diming Machine Operator	. J. Literine 140.			
- Control of the Cont	Water Well Contractor's C	ertification:			
	This well was drilled		liction a	nd this	report is
State of the state	true to the best of my kne	owledge and be	lief.	. 4	-
Was a drive shoe used? Tyes No Plugs Size: location ft.	Name Jany Burn	Mull D	rille	ry	•••••
Did any strata contain unusable water? Yes	(Ferson, firm or	corporation)	⁽³⁾ و	Type or pr	
There are markens don't of strata	Address 5543 S	es 1 Domes 1	- L -	<i>D</i> .4	<i>U</i>

Size of gravel: ..

[Signed]

Contractor's License No. 544 Date 6-6, 19.7