NC NOTICE TO WATER WELL CONTRACTOR NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to the filed with the filed with the state engineer, salem, or con grad 19 1968

STATE ENGINEER, SALEM, OR CON grad 19 1968

(Please type or print) (

State Well No. 2N/23-17 H	State Well No.	2N/23-	17 H
---------------------------	----------------	--------	------

State Permit No.

	- CARLON OF WELL		
1) OWNER:	(11) LOCATION OF WELL: County MOTTOW Driller's well nur	nber	
ctanler Magill	County 11022	R.23 E	W.M.
ddress Gecil, Oregon 97822	SE ¼ NE ¼ Section 17 T. 2N Bearing and distance from section or subdivision		
	500 feet north 500 feet west	from SE C	nner
2) TYPE OF WORK (check):	500 feet north 500 feet was a		
lew Well-	of Section 17, T2 N, R 23 E		
f abandonment, describe material and procedure in Item 12.	(12) WELL LOG: Diameter of well b	-less agging 1	211
3) TYPE OF WELL: (4) PROPOSED USE (check):	1	tod well 1.75	ft.
Rotary Driven Domestic Industrial Municipal Deble Detect Description Track Well Detect Description	Depth drilled 178 ft. Depth of comple		
Cable Jetted Irrigation Test Well Other	Formation: Describe color, texture, grain size and show thickness and nature of each stratus	m and aquifer	penetrated,
SING INSTALLED: Threaded Welded	and show thickness and nature of each status with at least one entry for each change of form	ation. Report of	each change cilling rates.
" Diam from 0 ft. to 90 ft. Gage	in position of Static Water Level as drilling par	From To	
" Diam from ft. to ft. Gage ft. Gage	MATERIAL		33
", Diam. fromft. toft. Gage	Soil, brown sandy		5 45
ERFORATIONS: Perforated? Yes 🛂 No.	gravel, yellow clay		30
	gravel, blue clay	80 120	
Type of perforator used Size of perforations in. by in. perforations from ft. to ft.	Clay blue, black cinder	120 170	
Size of perforations in. by in.	Clay blue, gray basalt	170 250	- 1
perforations fromft, toft.	Rock, mixed red & gray	250 32	. 1
perforations from It. to	Rock, red gray blue chiuci-	325 368	
perforations from ft. to ft.	Rock soft mixed clay	368 40	1
perforations fromft. toft.	Basalt, hard gray, red clay	100 43	5 54
perforations fromft. toft	Basalt, hard gray, blue clay	435 46	0
(7) SCREENS: Well screen installed? Yes No	Rock, soft mixed, blue clay	460 47	·
Manufacturer's Name	Basalt, hard gray	475 47	8 54
Type Model No.			
Diam Slot size Set from 1t. to		+	
Diam. Slot size Set from ft. to ft.		-	
(8) WATER LEVEL: Completed well.			
ft. below land surface Date 7/211/68			
an pressure lbs. per square inch Date			
(9) WELL TESTS: Drawdown is amount water level is lowered below static level		_ 	1 - 1
Was a pump test made? Yes No If yes, by whom?	Work started ADM 1 3	leted July 2	
gal./min. with ft. drawdown after hr	Date well drilling machine moved off of well		19
" " "	Drilling Machine Operator's Certification	a:	
" " " " " " " " " " " " " " " " " " " "			rision. Ma
Bailer test gal./min. with ft. drawdown after in	rials used and information reported at	love are true	; 60 1113 %
Artesian flow g.p.m. Date	Kilowieuge and School	Date	
Temperature of water Was a chemical analysis made? ☐ Yes ☐ I	No [Signed](Drilling Machine Operator)	Date illino	-
	Drilling Machine Operator's License No),	
(10) CONSTRUCTION:			
Well seal—Material usedBentonite Clay Depth of seal 60 feet in blue clay	ft. Water Well Contractor's Certification:		this reper
Diameter of well bore to bottom of sealin.	This well was drilled under my jur true to the best of my knowledge and b	elief.	errre rebor
Diameter of well bore to bottom of sear — Let Were any loose strata cemented off? ☐ Yes ★ No Depth			
Was a drive shoe used? ☐ Yes ☒ No	NAME (Person, firm or corporation)	(Type o	r print)
Was a drive snoe useur ☐ Tes 22 11 12 12 12 12 12 12 12 12 12 12 12	Address		
T. A. semente	TO M	. 1 /	,
Type of water	[Signed] Sanley Wolfe	agelle	,
Method of sealing strata off We No Size of gravel:	d(water west co	•	<u></u>
Was Well graver packed: [1] 100	Contractor's License No Date		19.
Gravel placed fromft. toft.	T CHEETS IF NECESSARY)		