## STATE OF OREGON

WATER WELL REPORT MORK 500 (as required by ORS 537.765)

AUG 21 1987

dage	4	Reco	لم
(for official	use on	ly)	

(1) OWNER:	(10) LOCATION OF WELL by legal description.	•	
Name PAUD CheNEY	County 747-000 Section	of _, WM.	
Address Star Rt 2	Township (Township is North or South), Range 23E (Range is East or West)	., 44 141.	
City Done ORC State 97843	Tax Lot Lot Block Subdivision		
(2) TYPE OF WORK (check):	MAILING ADDRESS OF WELL (or nearest address)		
New Well □ Deepening  Reconditioning  Abandon □			
If abandonment, describe material and procedure in Item 12.			
(A) PROPOSED LISE (check):	(11) WATER LEVEL of COMPLETED WELL:		
Rotary Air Driven Domestic Industrial Municipal D	Depth at which water was first found	ft.	
Thermal:	Static level ft. below land surface. Date	<del></del> ·	
Rotary Mud Dug Other:	Artesian pressure lbs. per square inch. Date	<del></del>	
Cable	(12) WELL LOG: Diameter of well below casing		
(5) CASING INSTALLED: Steel Plastic	Depth drilled ft. Depth of completed well ft.		
Threaded $\sqcup$ Welded $\sqcup$	Formation: Describe color, texture, grain size and structure of materials; and show th and nature of each stratum and aquifer penetrated, with at least one entry for each ch	nange or	
Diam. from ft. Gauge	formation. Report each change in position of Static Water Level and indicate pr	rincipal	
"Diam. from	water-bearing strata.	<u></u>	
LINER INSTALLED: Steel  Plastic   Threaded  Welded	WATERIAD	SWL	
1 meaded	Ream with 9 78" 33 266		
"Diam. fromft. to ft. Gauge	Bit & Stobolinger		
PERFORATIONS: Perforated?			
Size of perforations in. by in.	Bad offset at Button of		
perforations from	cases, and crooked from		
perforations from	90 to 130. was 8 from	·	
perforations from ft. to ft.	190 zv 266		
(7) SCREENS: Well screen installed?   Yes   No			
Manufacturer's Name		1006	
Type Model No		300G	
Type	Black 1, 275 297		
Diam Slot Size Set from ft. to ft.	LOST CIRC BLOCK 297 317		
Drowdown is amount water level is lowered	Black 317 325 Black 325 335		
(8) WELL TESTS: below static level			
Was a pump test made?    Yes  No If yes, by whom?			
Yield: gal./min. with ft. drawdown after hrs.	100016   Black 365 400 440		
, , , , , , , , , , , , , , , , , , ,	15n / Bleck 440 466		
Air test 300 gal./min. with drill stem at 300 ft. hrs.	00.1		
r test gal./min. with ft. drawdown after hrs.	- Seach		
Artesian flow g.p.m.			
Temperature of water 520 Depth artesian flow encountered ft.	Date work started 7-/6-87 /completed 8-/0-	87	
(9) CONSTRUCTION: Special standards: Yes \( \Dag{No} \)	Date well drilling machine moved off of well	1987	
seal—Material used	(unbonded) Water Well Constructor Certification (if applicable	e):	
rell sealed from land surface to	This well was constructed under my direct supervision. Materials u		
Diameter of well bore to bottom of seal in.	information reported above are true to my best knowledge and belief.		
Diameter of well bore below seal in.	[Signed]	9 -8-7	
Amount of sealing material sacks D pounds D			
How was cement grout placed?	(bonded) Water Well Constructor Certification:		
	Bond Issued by: (Surety Company Name)		
	On habelf of 12 RRY BURD Linell DRILLIAN	6 / N	
Was pump installed? Type HP Depth ft.	(type or print name of Water Well Constructor)		
Was a drive shoe used?	This well was drilled under my jurisdiction and this report is tru	e to the	
Ditt any strata contain analysis accept	best of my knowledge and belief:		
1, po 02 11 a 02 .	(Signed) Ley Buy		
Method of sealing strata off  Was well gravel packed?   Yes No Size of gravel:	(Water Well Constructor)		
	(Dated) 8 - 10 - 8		
Gravel placed from ft. to ft.	<u> </u>		