NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER WELL REPORT

STATE OF OREGON (Please type or print) State Well No. ...

ATER RESOURCES	DEPARTME	NT,	
SALEM, OREC within 30 days fr	ON 97318 om the date	MORR	504

(Do not write above this line) L 2 6 1978

	(10) LOCATION OF WELL:
(1) OWNER:	▼ 「 グー・ 」 「 「 」 「 「 」 「 」 「 」 「 」 「 」 「 」 「 」
Name DICH TREBS	County 1010111
Address CECIL ORP	NE 14 NE14 Section 19 T. 20 R. 23 E. W.M.
	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
	Depth at which water was first found 545 ft.
(8) 44-1-2-1	
Rotary Driven Domestic Industrial Municipal Cable Jetted D	Blatte 16401
Dug Bored Irrigation Test Well Other	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded Welded Welded tt. Gage tt. Gage Casta	(12) WELL LOG: Diameter of well below casing 8 % Depth drilled 240 ft. Depth of completed well 665 ft.
" Diam. fromft. toft. Gage " Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
PERFORATIONS: Perforated? Yes No.	
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	BASALT BIRCH 5 15 425 4417
perforations from ft. to ft.	11 BLOCK 447 545
perforations from	11 Bleck 5/5 545 625 1120
perforations fromft. toft.	Black 6-25 665
(7) SCREENS: Well screen installed? Yes Z-No	
Manufacturer's Name	
TypeModel No.	
Diam Slot size Set from ft. to ft.	
Diam. Slot size Set from ft. to ft.	
(8) WELL TESTS. Drawdown is amount water level is	
lowered below static level	
Was a winder test made? If Yes No If yes, by whom? PR/LLCE	
Yield: 800 gal./min. with 300 ft. drawdown after / hrs.	
" " "	
" - "	
Bailer test gal./min. with ft. drawdown after hrs.	
Artesian flow g.p.m.	25 1 70 075
perature of water 72 Depth artesian flow encountered ft.	Work started (~ 29 19 78 Completed 6-30 1978
(A) CONCERNICATION	Date well drilling machine moved off of well 6 3 c 19 73
(9) CONSTRUCTION:	Drilling Machine Operator's Certification:
Well seal—Material used	This woll was constructed under my direct supervision.
Well sealed from land surface toft.	Materials used and information reported above are true to my
Diameter of well bore to bottom of seal in.	best knowledge and belief. [Signed] Fary Burd Date 6-30, 1978
Diameter of well bore below sealin.	(Driffing Machine Operator)
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No. 933
How was cement grout placed?	
The state of the s	Water Well Contractor's Certification:
	This well was drilled under my jurisdiction and this report is
	true to the best of my knowledge and belief.
Was a drive shoe used? ☐ Yes ☑ No Plugs Size: locationft.	Name Jan Bull Dulling (Berson, firm or corporation) (Type or print)
Did any strata contain unusable water? 🗌 Yes 🍎 No	7 7 7 7 7
Type of water? depth of strata	Address Pendleton or
Method of sealing strata off	[Signed] Lang Burd
Was well gravel packed? Tes INO Size of gravel:	(Water Well Contractor)
Gravel placed from	Contractor's License No. 544 Date 6-36, 1978
Gravet placed from	