

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT
SALEM, OREGON 97331
within 30 days from the date of well completion.

WATER WELL REPORT
STATE OF OREGON
(Please type or print)

RECEIVED

RECEIVED

APR 18 1978

(Do not write above this line)

MARR 509
MAY 17 1978

State Well No. 2N/24E-31
State Permit No. G-6920 Appl.

(1) OWNER: WATER RESOURCES DEPT.
SALEM, OREGON
Name Roy Lindstrom
Address R.R. 1, ONE, OREGON

(2) TYPE OF WORK (check):
New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL: (4) PROPOSED USE (check):
Rotary Driven Domestic Industrial Municipal
Cable Jetted Irrigation Test Well Other
D Bored

CASING INSTALLED: Threaded Welded
14" Diam. from 0 ft. to 50 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS: Perforated? Yes No.
Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS: Well screen installed? Yes No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? Yes No If yes, by whom? MORGAN GRAIN GEARS.
gal./min. with ft. drawdown after 4 hrs.
1500 G.P.M. " " "
Bailer test gal./min. with ft. drawdown after hrs.
an flow g.p.m.
ature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used NEAT CEMENT
Well sealed from land surface to 50 ft.
Diameter of well bore to bottom of seal 18 in.
Diameter of well bore below seal 12 in.
Number of sacks of cement used in well seal 20 sacks
How was cement grout placed?
Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL: (#3 USB)
County MORROW, Driller's well number 04-78
SE 1/4 SE 1/4 Section 31 T. 2N R. 24 E. W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found 350 ft.
Static level 318 ft. below land surface. Date 3-18-78
Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 12" TO 500'
Depth drilled 1111 ft. Depth of completed well 1111 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
SILT SOIL	0	21	
CLAY	21	36	
MED. HARD GREY BASALT	36	105	
BROKEN	105	120	
SOFT RED	120	155	
MED. " " "	155	260	
HARD	260	350	
BROKEN	350	370	water
HARD	370	435	
SOFT	435	450	
MED.	450	680	
MED.	680	850	
VERY HARD	850	980	
MED.	980	1012	
BROKEN	1012	1111	water

Work started 2-14 1978 Completed 3-1 1978
Date well drilling machine moved off of well 3-1 1978

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] [Signature] Date 3-14, 1978
(Drilling Machine Operator)
Drilling Machine Operator's License No. 886

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name WALLACE WEBB DRIBBLING
(Person, firm or corporation) (Type or print)
Address PENDLETON, OREGON
[Signed] [Signature]
(Water Well Contractor)
Contractor's License No. 583 Date 3-14, 1978