STATE OF OREGON WATER SUPPLY WELL REPORT

(as required by ORS 537.765)

WELL I.D. #L 76842 START CARD # 166242

Instructions for completing this report are on the last page of this form.	(A) LOCATION OF WELL (local description)
(1) LAND OWNER Well Number	(9) LOCATION OF WELL (legal description) County Markow
Address 76025 FRONTAGE ROAD	Tay Lot 300 Lot
City HERMISTON State OREGIN Zip 97838	Township 4N OP or S Range 275 OP or W WM
	Section /9 SW 1/4 Sk/ 1/4
(2) TYPE OF WORK New Well	(dermes or decima)
☐ Deepening ☐ Alteration (repair/recondition) ☐ Abandonment ☐ Conversion	Lat or (degrees or decimal tong or (degrees or decimal tong or (degrees or decimal tong or or or (degrees or decimal tong or or or or
	•
(3) DRILL METHOD ☐ Rotary Air ☐ Rotary Mud ☐ Cable ☐ Auger ☐ Cable Mud	Street Address of Well (or nearest address)
Other	
U Oulei	(10) CTATIONIATED I EVEY
(4) PROPOSED USE	(10) STATIC WATER LEVEL //3' ft. below land surface. Date 5/17/05
Domestic Community Industrial Irrigation	• •
Thermal Injection Livestock Other	ft. below land surface. Date
(5) BORE HOLE CONSTRUCTION Special Construction: Yes No	Artesian pressure lb. per square inch Date
Denth of Completed Well 185 ft	(11) WATER BEARING ZONES
Explosives used: Yes No Type Amount	(11) WATER BEARING ZONES Depth at which water was first found /42
BORE HOLE SEAL	From To Estimated Flow Rate SWL
Diameter From To Material From To Sacks or Pounds	142 185 0 113
24" 0 18 BENTONTE 18" 0 36 SAUS	
20' 18' 185	
How was seal placed: Method A B ZC D E	
Other	(12) WELL LOG Ground Elevation
Backfill placed fromft. toft. Material	Material From To SWL
Gravel placed from ft. to ft. Size of gravel	SAND 0 43' 142'
	10 FAVEL 142' 185 113'
(6) CASING/LINER Diameter From To Gauge Steel Plastic Weided Threaded	
Casing: 20' +2' 185' 375 20	
Liner:	BEACTURE
	HEGEIVED
Liner:	
	MAY 2 3 2005
Drive Shoe used ☐ Inside ☑ Outside ☐ None	
Final location of shoe(s) 185	WATER RESOURCES DEPT
(7) PERFORATIONS/SCREENS	SALEM, OREGON
Perforations Method	
Screens Type Material	Date Started 04/12/05 Completed 05/17/05
From To Slot Númber/Diameter Tele/pipe Casing Liner	(unbonded) Water Well Constructor Certification
fize / /// size	I certify that the work I performed on the construction, deepening, alteration,
	abandonment of this well is in compliance with Oregon water supply well
	construction standards. Materials used and information reported above are true to the best of my knowledge and belief.
	uie best of my knowledge and belief.
	WWC Number 1731 Date 05/17/05
(8) WELL TESTS: Minimum testing time is 1 hour	1 South
Pump Bailer Air Flowing Artesian	Signed
Yield gal/min Drawdown Drill stem at Time	(bonded) Water Well Constructor Certification
O 185' 14 R	I accept responsibility for the construction, deepening, alteration, or
	abandonment work performed on this well during the construction dates reported above. All work performed during this time is in compliance with Oregon water
	supply well construction standards. This report is true to the best of my knowledge
Temperature of water Depth Artesian Flow Found	and belief.
Was a water analysis done? Tes By whom	WWC Number 544 Pate 5/17/05
Did any strata contain water not suitable for intended use?	WWC Number
Salty Muddy Odor Colored Other	Signed Jany Buy
Depth of strata:	Signed