

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

RECEIVED WATER WELL REPORT

STATE ENGINEER, SALEM, OREGON within 30 days from the date of well completion

STATE OF OREGON (Please type or print) Do not write above this line

STATE ENGINEER SALEM, OREGON

MORR 513

State Well No.

2N/24-32ad

State Permit No.

5-4727

Appl. G-5014

(1) OWNER:

Name Lindstrom Bros. Address Lane, Ore.

(2) TYPE OF WORK (check):

New Well [x] Deepening [] Reconditioning [] Abandon []

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [x] Driven [] Cable [] Jetted [] Dug [] Bored []

(4) PROPOSED USE (check):

Domestic [] Industrial [] Municipal [] Irrigation [x] Test Well [] Other []

CASING INSTALLED:

1.8" Diam. from 0 ft. to 28 ft. Gage 1025
1.6" Diam. from 0 ft. to 28 ft. Gage 1025

PERFORATIONS:

Perforated? [] Yes [x] No

Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? [] Yes [x] No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.

(8) WATER LEVEL: Completed well.

Static level 272 ft. below land surface Date
Artesian pressure lbs. per square inch Date

(9) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? [x] Yes [] No If yes, by whom?
Yield: 1100 gal./min. with 125 ft. drawdown after 10 hrs.

Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m. Date
Temperature of water Was a chemical analysis made? [] Yes [] No

(10) CONSTRUCTION:

Well seal-Material used Cement
Depth of seal 0-28' ft.
Diameter of well bore to bottom of seal 28" in.
Were any loose strata cemented off? [] Yes [x] No Depth
Was a drive shoe used? [] Yes [x] No
Did any strata contain unusable water? [] Yes [x] No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? [] Yes [x] No Size of gravel:
Gravel placed from ft. to ft.

(11) LOCATION OF WELL:

County Morrow Driller's well number #2
SE 1/4 NE 1/4 Section 32 T. 2N R. 24E W.M.
Bearing and distance from section or subdivision corner

(12) WELL LOG:

Diameter of well below casing 14 1/2"
Depth drilled ft. Depth of completed well 124 1/2" ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

Table with columns: MATERIAL, From, To, SWL. Rows include Soil, Brown Sandy, Basalt, Red, Basalt, BIK Hard, Basalt, Black, porous, Basalt, Black, Hard, Basalt, Black porous, Claystone, Basalt BIK, Hard, Basalt, Gray very hard, Basalt, Black broken, Claystone, Basalt, Gray, Basalt, Black porous, Basalt, Gray Hard, Basalt, Black, soft, Basalt, Gray, Hard, Soft Porous Black Basalt, Hard Black Basalt, Med Soft BIK Basalt, Soft " " + Cinders, Med Hard Black Basalt.

Work started Sept 19 1964 Completed Dec 14 1969
Date well drilling machine moved off of well 12-14-69 19

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Al Ellsworth (Drilling Machine Operator) Date Dec 30 1969
667 (Ellsworth)
Drilling Machine Operator's License No. 640 (Perry)

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME Project Corporation (Type or print)
Address #100 Second, Walla Walla, W.W.
[Signed] Cateblood (Water Well Contractor)
Contractor's License No. 512 Date 1-5-1970