MORR 51395

STATE OF OREGON			0200		<u> </u>
WATER SUPPLY WELL REPORT	WELL I.D. # L_ <u><i>R</i> 328/</u> START CARD #_ <u>/60438</u>				
(as required by ORS 537.765) Instructions for completing this report are on the last page of this form.	S	IART CARL)*_/60	438	
(1) LAND OWNER	(9) LOCATION OF WELL by legal description: County Morrow Latitude Longitude				
Address 822 Hwy. 395 South # 423	Township <u>4N</u> N or S Range <u>26E</u> E or W. WM.				
City Hermiston State OR Zip 97838	$\frac{10 \text{ wnsnip}}{10 \text{ section}} = \frac{17}{17} = \frac{14}{14} = \frac{14}$				
(2) TXPE OF WORK	Section JA 1/4 JA 1/4				
Wew Well Deepening Alteration (repair/recondition) Abandonment					
	Street Address of Well (between Patter son	Ferry Rel	and Dom	bine Re	nec Ro
(3) DRILL METHOD: Protary Air CRotary Mud Cable Auger	(10) STATIC WATER I		Boahama	A, OR 9	7818
□ Other	$fi.$ below land surface. Date $\frac{4}{2}$				
(4) PROPOSED USE:	Artesian pressurelb. per square inch Date				
Domestic Community Industrial Infrigation	(11) WATER BEARING				
Thermal Injection Livestock Other		J 201120.	1.1		
(5) BORE HOLE CONSTRUCTION	Depth at which water was fi	rst found			
Special Construction approval TYes PNo Depth of Completed Well 20st.	From To		Estimated Flow Rate SW		SWL
Explosives used Yes INO TypeAmount	14	90	20	00	1
HOLE SEAL	90	110		00	17
Diameter From To Material From To Sacks or pounds	110	120	50	20+	1/
16" 20 120					
					1
	(12) WELL LOG:				
How was seal placed: Method A B C D E		levation			
Pother Poured 3/2" bentonite					1
Backfill placed fromft. Material	Material		From	To	SWL
Gravel placed fromft. toft. Size of gravel	Sandy soil			\downarrow	ļ
(6) CASING/LINER:	Black sand			14	┼────
Diameter From To Gauge Steel Plastic Welded Threaded Casing:	Brown Sand		_14	90	WB
	Sand & grave/		90	110	WB
	Sandy grave		110	120	WB
				· [╉────
Liner: 14" 99 119 250 12 0 12					{
					╅────
Drive Shoe used Inside Dutside None	<u>├</u>			┥━╸──	┼───
Final location of shoe(s)					┼
(7) PERFORATIONS/SCREENS:				+	┼───-
Perforations Method Toreheut				┽╍╼╼╍	+
Stot Screens Stot Stot Stot Stot Stot Stot Stot Sto				┼╼╸┈	┼───
From To size Number Diameter size Casing Liner	DECEIVE			-	
99 119 Srows "4" 14" 0					<u> </u>
	SEP 2 5 200	6 7			
		1		<u>-</u>	
	WATER RESOURCES	N			1
(8) WELL TESTS: Minimum testing time is 1 hour	WATER RESOURCES	Con	npleted 4	-24-0	6
Flowing	(unbonded) Water Well Con		·		
Pump Bailer Kir Artesian	I certify that the work I pe			eration, or aba	undon-
Yield gal/min Drawdown Drill stem at Time	ment of this well is in complia	nce with Orego	n water supply v	vell constructi	on
1,000+ 120 lhr.	standards. Materials used and knowledge and belief.	information rep	orted above are i	true to the bes	tofmy
			WWC Nu	mber	
	Signed			Dale	
Temperature of water Depth Artesian Flow Found	(bonded) Water Well Constr	uctor Certifica	tion:		
Was a water analysis done? Yes By whom	I accept responsibility for	the construction	n, alteration, or :	bandonment	work
Did any strata contain water not suitable for intended use?	performed on this well during performed during this time is l				
Salty Muddy Odor Colored Other	construction standards. This re	port is true to th	e best of my kn	owledge and l	belief.
Depth of strata:	At 1	1,], D	🖌 WWC Nu	mber	18
	Signed a Auch	vura	1	<u>ستکب</u> علام	-06

ORIGINAL - WATER RESOURCES DEPARTMENT FIRST COPY - CONSTRUCTOR SECOND COPY - CUSTOMER