MORR 52132

STATE OF OREGON WATER SUPPLY WELL REPORT (as required by ORS 537,765 & OAR 690-205-0210)

WELL LABEL # L	96347
START CARD #	1010114

(1) LAND OWNER Owner Well I.D. Inland Well 3	(9) LOCATION OF WELL (legal description)
First Name R.D. Last Name Offut	County MORROW Twp 3 N N/S Range 24 E E/W WM
Company Threemile Canyon Farms	Sec 13 NE 1/4 of the SE 1/4 Tax Lot 100
Address 75906 Threemile Road	Tax Map Number Lot
City Boardman State OR Zip 97818	Lat ' or 45.74593 DMS or DD
(2) TYPE OF WORK New Well Deepening Conversion	Long or -119.763893 DMS or DD
Alteration (repair/recondition) Abandonment	Street address of well • Nearest address
	Tower Road and Radar Range Road
(3) DRILL METHOD Rotary Air Rotary Mud Cable Auger Cable Mud Reverse Rotary Other	(10) STATIC WATER LEVEL
	Existing Welf / Predeepening Date SWL(psi) + SWL(ft)
(4) PROPOSED USE Domestic Irrigation Community	Completed Well 05-11-2013 189.8
Industrial/Commercial Livestock Dewatering	Flowing Artesian? Dry Hole?
Thermal Injection Other	WATER BEARING ZONES Depth water was first found 153
(5) BORE HOLE CONSTRUCTION Special Standard Attach copy)	SWL Date From To Est Flow SWL(psi) + SWL(ft)
Depth of Completed Well 926 ft.	03-05-2013 153 173 100 62
BORE HOLE SEAL sacks/	03-09-2013 264 279 200 185
Dia From To Material From To Amt lbs	04-10-2013 563 658 5,000 192.75
30 0 86 Cement 0 86 88 S	04-21-2013 785 795 5,000 191.3
24 86 610 Cement 0 545 558 S	04-24-2013 868 906 5,000 191.3
	(11) WELL LOG Ground Elevation 608
How was seal placed: Method A B C D E	Material From To
Other	Notes:
Backfill placed from ft. to ft. Material	Mud roatary drilling - 0-86ft
Filter pack from ft. to ft. Material Size	Direct air rotary drilling - 86ft-620ft
Explosives used: Yes Type Amount	Reverse air rotary drilling - 620ft-926ft
(6) CASING/LINER	silty fine sand caliche at 17 0 17
Casing Liner Dia + From To Gauge Stl Plstc Wld Thrd	red/brown clay 17 57
② 26 □ 0 86 .375 ② X □	weathered basalt 57 86
② 20 🗶 1 545 .375 🔘 🗶	hard basalt Blue green clay RECEIVED BY OWR 26 142 153
	soft vesicular basalt
	green claystone AUG 3 0 2013 282 292
Shoe Inside Outside Other Location of shoe(s)	soft vesicular basalt 292 300
Temp casing Yes Dia From To	hard basalt glassy texture 300 434
(7) PERFORATIONS/SCREENS	green claystone SALEM, OR 434 466
Perforations Method	soft vesicular basalt 466 484
Screens Type Material	hard basalt 484 553
	green claystone (thin >1ft) 553 554
Perf/S Casing/Screen Scrn/slot Slot # of Tele/ creen Liner Dia From To width length slots pipe size	Date Started 02-25-2013 Completed 04-25-2013
110m 10 widar lengar 500 ppc size	(unbonded) Water Well Constructor Certification
	I certify that the work I performed on the construction, deepening, alteration, or
	abandonment of this well is in compliance with Oregon water supply well
	construction standards. Materials used and information reported above are true to
(O) EVENT I PROPER LA	the best of my knowledge and belief.
(8) WELL TESTS: Minimum testing time is 1 hour	License Number 1937 Date 08-19-2013
● Pump ☐ Bailer ☐ Air ☐ Flowing Artesian	Password : (if filing electronically) Signed
Yield gal/min Drawdown Drill stem/Pump depth Duration (hr)	
4,000 21 502 77	(bonded) Water Well Constructor Certification
	I accept responsibility for the construction, deepening, alteration, or abandonment
The second of th	work performed on this well during the construction dates reported above. All work
Temperature 71 °F Lab analysis X Yes By Anatek Labs	performed during this time is in compliance with Oregon water supply well construction standards. This report is true to the best of my knowledge and belief.
Water quality concerns? Yes (describe below) From To Description Amount Units	
Third Child	License Number 1934 Date 08-19-2013 Password: (if filing electronically)
	Signed Signed
	Contact Info (ortional)

MORR 52132

WATER SUPPLY WELL REPORT - continuation page

WELL I.D. # L 96347	
START CARD # 1019114	,

(5) BORE HOLE CONSTRUCTION	(10) STATIC WATER LEVEL
BORE HOLE SEAL sacks/	Water Bearing Zones
Dia From To Material From To Amt lbs	Water Dearing Zones
	SWL Date From To Est Flow SWL(psi) + SWL(ft)
FILTER PACK	
From To Material Size	
	(44) WELL LOC
(6) CASING/LINED	(11) WELL LOG
(6) CASING/LINER	Material From To
Casing Liner Dia + From To Gauge Stl Plstc Wld Thrd	weathered basalt 554 563
	broken vesicular red & black basalt monster cuttings 563 658
K XI — F I K XI F I	hard basalt 658 779
K AL TITLE K A H H I	soft weathered vesicular basalt (thin) 779 781 hard basalt 781 785
	hard basalt 781 785 hard soft vesicular basalt 785 795
	hard basalt 795 868
	soft vesicular basalt 868 908
	hard basalt 908 926
(7) PERFORATIONS/SCREENS	
• •	
Perf/S Casing/Screen Scrn/slot Slot # of Tele/ creen Liner Dia From To width length slots pipe size	
110111 10111 101111 1011111111111111111	
(8) WELL TESTS: Minimum testing time is 1 hour	
Yield gal/min Drawdown Drill stem/Pump depth Duration (hr)	Comments/Remarks
Water Quality Concerns	
	RECEIVED BY OWRD
From To Description Amount Units	
	בוחכ מפ חווא
	AUG 3 0 2013
	SALEM, OP
	OALLIN, OI

MORR 52132

WATER SUPPLY WELL REPORT - continuation page

WELL I.D. # L 96347

START CARD # 1019114

Inland Well #1 Onland Well #2

Inland Well #5

Inland Well #3

Inland Well #4

Image = 2004 Objiniciabe

Google earth

RECEIVED BY OWRD

AUG 3 0 2013

SALEM, OR