NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the WATER WELL REPORT	
WATER RESOURCES DEPARTMENT, MAR 23 198 STATE OF OREGON HOPE 527 State Well No. 21/2664	
within 30 days from the date of well completion. WATER RESOURCES DEPT	State Permit No KKCOCK
OALEN, ORRGON	
(I) OWNER:	(10) LOCATION OF WELL:
Name Baardman Farms	County Driller's well number
Boradoren Orl	NW 14 SE 14 Section 6 T. 2N R. 26E W.M.
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner
New Well ☐ Deepening ☐ Reconditioning	nvell # 2 920'
If abandonment, describe material and procedure in Item 12.	(11) YVA MIND T NIVEY C
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed well.
Rotery D Driven D	Depth at which water was first found VA ft.
Jetted Domestic Industrial Municipal	Static level 3.59 ft. below land surface. Date 3~17-67
Trigutant & Tast well Other	Artesian pressure lbs. per square inch. Date
5) CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing 15/4
" Diam. from ft. to ft. Gage	Depth drilled ft. Depth of completed well / 188 ft.
"Diam. from A. ft. to	Formation: Describe color, texture, grain size and structure of materials;
" Diam. from ft. to ft. Gage	and show thickness and nature of each stratum and aguifer penetrated
PERFORATIONS:/ Perforated? Yes No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	Run 14 3/4 " Bit +
perforations from	Stabalize to Botton
perforations from ft. to ft.	to clean out Botto
perforations from ft. to ft.	
(7) SCREENS: Well screen installed? Yes No	
Manufacturer's Name	
Type Model No	
Diam Slot size Set from ft. to ft.	
Diam. Slot size from ft. to ft.	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
a pump test made? No If yes, by whom?	
Viold:	
gai./min. with it. drawdown after hrs.	
" " "	
Beiler test gal./min. with ft. drawdown after hrs.	
Artesian flow g.p.m.	
emperature of water 75 Depth artesian flow encountered ft.	West about 2 = 12 = 15 = 15 = 15 = 15 = 15 = 15 =
	Work started 3-/7 1987 Completed 3-/9 1987
(9) CONSTRUCTION:	Date well drilling machine moved off of well 3-/9 1987
Well seal—Material used	Drilling Machine Operator's Certification:
Well sealed from land surface toft. Diameter of well bore to bottom of sealin,	This well was constructed under my direct supervision. Materials used and information reported above are true to my
Diameter of well bore below seal	best knowledge and belief.
Number of sacks of cement used in well seal sacks	[Signed] Date 3-19, 19.87
How was cement grout placed?	Drilling Machine Operator's License No. 544
A A A A A A A A A A A A A A A A A A A	Water Well Contractor's Certification:
- Administration of the second	This well was drilled under my jurisdiction and this report is
Was a drive shoe used? ☐ Yes ☐ No Plugs Size: location ft.	true to the best of my knowledge and belief.
Did any strata contain unusable water? Yes No	Name Javy Burd Well Drilling 1. (Pyson, firm or corporation) (Type or print)
Type of water? depth of strata	Address 5543 S. W. Douglas Parl Color
Method of sealing strata off	
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	[Signed] (Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No. 549 Date 3-19 , 1987
(USE ADDITIONAL SHEETS IF NECESSARY) SP*45656-119	