NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT

(Please type or print)

STATE OF OREGON MORR 546

(Do not write above this line)

State	well No.	20/26-26.	40
State	Permit No.		

(1) OWNER:	(10) LOCATION OF WELL:		
Name James Klukkerk	County Morrow Driller's well number		
Address Star Regit	SW. 1/4 SE 1/4 Section 26 T. 7-71, R. 26 E. W.M.		
Echs, Oregon 97826	Bearing and distance from section or subdivision corner		
(2) TYPE OF WORK (check):			
New Well ☐ Deepening ≰ Reconditioning ☐ Abandon ☐			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found ft.		
Rotary Driven Domestic Manicipal Domestic Municipal Domestic Notation	Static level 200 ft. below land surface. Date 5-22-80		
Bored   Irrigation   Test Well   Other	Artesian pressure lbs. per square inch. Date		
CASING INSTALLED: Threaded   Welded	(12) WELL LOG: Diameter of well below cooling 84		
Diam. fromft. toft. Gage	Cashing		
" Diam. from ft. to ft. Gage	Depth drilled 205 ft. Depth of completed well 408 ft.		
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,		
C) DEDECT AMICNIC	with at least one entry for each change of formation. Report each change in		
PERFORATIONS: Perforated?  Yes No.	position of Static Water Level and indicate principal water-bearing strata.		
Type of perforator used	MATERIAL From To SWL		
Size of perforations in. by in.	Basalt 203 327		
perforations from ft. to ft.	Basal Land, gray 327 345		
perforations from ft. to ft.	Kock, Med., black 0 345 408 W.B.		
perforations from ft. to ft.			
(7) SCREENS: Well screen installed?   Yes X No			
Manufacturer's Name			
Type Model No.			
Diam Slot size Set from ft. to ft.			
Diam Slot size Set from ft. to ft.			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	- REGEIVED		
a pump test made? MYes 🗌 No If yes, by whom?	JUN <b>1</b> 9 1980		
Yield: 48 gal./min. with 5 ft. drawdown after 24 hrs.	WATER RESOURCES DEPT		
n n n	SALEM, OREGON		
" " 11 "	BALLIN OTHOUT		
Beiler test gal./min. with ft. drawdown after hrs.			
esian flow g.p.m.			
emperature of water Depth artesian flow encountered ft.	Work started 5-13 1980 Completed 5-22 1980		
(9) CONSTRUCTION:	Date well drilling machine moved off of well 5.22 1980		
Well seal—Material used not disturbed			
Well seal—Material used Nov. Account Drilling Machine Operator's Certification:  Well sealed from land surface toft.  This well was constructed under my direct supervisi			
Diameter of well bore to bottom of sealin.	Materials used and information reported above are true to my best knowledge and belief.		
Diameter of well bore below sealin.	[Signed] James Thetel Date 5-22 1980		
Number of sacks of cement used in well seal sacks	(Drilling Mackine Operator)		
How was cement grout placed?	Drilling Machine Operator's License No. 445		
	Water Well Contractor's Certification:		
	This well was drilled under my jurisdiction and this report is		
Was a drive shoe used? ☐ Yes ☐ No Plugs Size: location ft.	true to the best of my knowledge and belief.		
Did any strata contain unusable water?   Yes  No  No	Name TRAU GRIFFIH  (Person, firm or corporation) (Type or print)		
Type of water? depth of strata	Address 900 HERMI STON AVE, HERMI STON ORE		
Method of sealing strata off	The II The TIEN IN THE PARTY OF		
	[Signed] My Dougle (Water West Contractor)		
	<u> </u>		
Gravel placed from ft. to ft.	Contractor's License No. 65 Date 5-22 , 1986		