NOTICE TO WATER WELL CONTRACTOR  The original and first copy of this report  are to be filed with the	L REPORT	1 - 11	
WATER RESOURCES DEPARTMENT STATE OF	OREGON State Well No. NOW E	/Ddb	
SALEM, OREGON 97310 FEB 7 100 (Please type		,	
SALEM, OREGON 97310  Within 30 days from the date ATER RESOURCES  SALEM DEPTH OF THE SALE	ove this line) State Permit No	***************************************	
	(10) TOCAMION OF WELL.		
	(10) LOCATION OF WELL:		
Name William Sullivan	County Morrow Driller's well number 47		
Address F.O. HOX 7, Downgry, Cro	WW 145 E 14 Section / P T. 3. 11/R. 26 E W.M.		
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner		
New Well   Deepening □ Reconditioning □ Abandon □	300 South & 75 E. of the New, Cox,		
If abandonment, describe material and procedure in Item 12.	1 5. L /14 of Soci 10		
	(12) WATER LEVEL: Completed well.	メ	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 165. — ft.		
Domestic Mindustrial   Municipal	Static level 120, 2 ft. below land surface. Date A	reg 29/79	
☐ Bored ☐ Irrigation ☐ Test Well ☐ Other ☐	Artesian pressure NOVE lbs. per square inch. Date	4929/79	
(5) CASING INSTALLED: Threaded ☐ Welded 🕅	(10) MARKET LOCK	9"	
8 "Diam. from 7 1. 5 ft. to 178.5 ft. Gage . 250	and a	0 2 02	
" Diam. fromft. toft. Gage		83,≤ft.	
" Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size and structure of and show thickness and nature of each stratum and aquifer p	penetrated,	
6) PERFORATIONS: Perforated? Tilyes Vino.	with at least one entry for each change of formation. Report each position of Static Water Level and indicate principal water-bear		
6) PERFORATIONS: Perforated? Tyes No.  Type of perforator used	MATERIAL From To	SWL	
Size of perforations — in. by in. 2	SILTU SONDY TOP SOIL 0, 2 42	2	
perforations fromft. toft.	Cocres are cond 4: 61:	<u>e</u>	
perforations fromft. toft.	Lt. Brown Clay 610 1/65	2	
perforations from ft. to ft.	white sand & Gravel 1650 171.3	2	
(7) CODEENC.	Soft Brown Boselt 171: 180:	9 171.	
(7) SCREENS: Well screen installed?   Yes   No	Black Basalt 1805265.	= 110.3	
Manufacturer's Name	Grey Bosalt 265. 287.		
Diam. Slot size Set from ft. to ft.	Blue class 322 354	<del></del>	
Diam. Slot size Set from ft. to ft.		\$120,0	
(8) WELL TESTS: Prawdown is amount water level is	Hole from 171, 2 to 178,5 0,000	rac sem	
lowered below static level	grouted with to sacks come	190041	
a pump test made? Yes M No If yes, by whom?	then aging the to 178, 3	120	
Yield: 60 gal./min. with 100 ft. drawdown after //2 hrs.	Let set to - VEUN IN	HEU	
ll II I	SEP 17 1979 NOV - 0.19	179	
<i>n</i>	WATER RESOURCES DWATER RESOURCE		
Bailer test Legal./min. with Left. drawdown after hrs.	- OALEM, ORECON	ES DEPT	
sian flow NONE g.p.m.	EALEM, ORE	GON	
remperature of water 55 Depth artesian flow encountered ITAN Ett.	Work started Aug. 16 197 9 Completed Aug 29	9 1979	
(9) CONSTRUCTION:	Date well drilling machine moved off of well Aug 30	1979	
Well seal-Material used Cement Grout	Drilling Machine Operator's Certification:	,	
Well sealed from land surface toft.	This well was constructed under my direct supe Materials used and information reported above are tru	ervision.	
Diameter of well bore to bottom of seal	best knowledge and belief	_	
Diameter of well bore below seal 93/4 the shire shoe	[Signed] Date Machine Operator)	Z, 1978	
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No.	<b>3</b>	
How was cement grout placed? Com ent Grout Trem-			
Surface casing, Filled Annular	Water Well Contractor's Certification:		
space to ground hevel	This well was drilled under my jurisdiction and this	report is	
Was a drive shoe used? Yes 🗆 No Plugs Size: location ft.	true to the best of my knowledge and belief.		
Did any strata contain unusable water? 🗌 Yes 🗗 No	Name Sylvida E Trum Dylling (Type or print)		
Type of water? depth of strata	Address P. Da DOX 124, Hermis ton,	aregen	
Method of sealing strata off	[Signed] John I Brown 9	7838	
Was well gravel packed? ☐ Yes MNo Size of gravel:	(Water Well Contractor)		
Gravel placed from ft. to ft.	Contractor's License No. 5/6 Date Sept 5	, 19.7.2	
(USE ADDITIONAL SH	EETS IF NECESSARY)	SP*45	



Oregon Water Resources Department 725 Summer Street NE, Suite A Salem Oregon 97301 (503) 986-0900 www.oregon.gov/owrd

## Application for Well ID Number

Do not complete if the well already has a Well Identification Number.

RECEIVE	n

	JUN 3 2024
I. OWNER INFORMATION	OWRD
Current Owner Name (please print): Ten Post LLC	OWED
Mailing Address: 3620 Independence Rd	
City, State, Zip: Sunnyside, WA 98944	
Mail Well ID to: SAME AS ABOVE In Care Of (C/O)	
Name & Address:	
City, State, Zip:	
II. WELL LOCATION INFORMATION (Please fill out as completely as possible)  Township: 3N (North / South) Range: 26E (East / West) Section: 10 NE 1/4  Tax Lot (usually last 3-5 numbers of Tax Map #): 1000 County Morrow  GPS Coordinates: 45.753715° / -119.549874° (WGS 84)  Street Address of Well, City: 74271 Homestead Ln, Hermiston, OR 97838  If the property had a different street address in the past:	4 of the <u>SW</u> 1/4
III. GENERAL WELL INFORMATION (Please fill out as completely as possible, AND attach copy of Well Report, Use of Well (domestic, irrigation, commercial, industrial, monitoring):  Domestic and Commercial  Date Well Constructed (or property built):  8/29/1979  Total Well Depth:  383 feet  Casing  Owner at time the well was constructed (if known):  Well Report # (if known):	Diameter: 8-inch
SUBMITTED BY (please print): Brian Bosma  PHONE: (509) 391 – 1111 EMAIL &/or FAX: 1500 Dosma & gmail  To send the completed application, you may MAIL it to: Oregon Water Resources Dept. 725 Summer 5t NE, Suite.  Or EMAIL the completed PDF form to: Ladeena.K.Ashley@water.oregon.gov, or FAX it to: (503) 986-0902.	
For Official Use Only by the Oregon Water Resources Department:	
Received Date: Well Report Number:  6-3-2024 MORR 600	Well Identification #: L-154741