NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

MOVER LOLOO (Do not write above this line

state Well No.

State Permit No.

(1) OWNER:	(10) LQCATION OF WELL:	
Name Larry Eades	County Moure Driller's well number	
Address Pt 1 Box 22-A.	SE 14 SE 14 Section 14 T. 471. R. 24E.	W.M.
Boudman, Olegon 97818	Bearing and distance from section or subdivision corner	VV .1V1.
(2) TYPE OF WORK (check): V	Searing and distance from section of subdivision corner	
New Well 🗌 Deepening 💢 Reconditioning 🗍 Abandon 🗀		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	ft.
Domestic Municipal Domestic	,	-23-80
Dag 🗌 Bored 🗋 Irrigation 🔀 Test Well 🗎 Other 📋	Artesian pressure lbs. per square inch. Date	
5) CASING INSTALLED: Threaded [] Welded [] (1) Welded [] (2) Welded [] (3) Welded [] (4) Welded [] (5) Welded [] (6) Welded [] (6) Welded [] (7) Welded [] (7) Welded [] (8) Welded [] ((12) WELL LOG: Diameter of well below casing 6.4.	160-72
" Diam. fromft. Gage	Depth drilled 265 ft. Depth of completed well 724	ft.
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of m	naterials;
6) PERFORATIONS: Perforated? Yes No.	and show thickness and nature of each stratum and aquifer pe- with at least one entry for each change of formation. Report each c position of Static Water Level and indicate principal water-bearin	hange in
Type of perforator used	MATERIAL From To	swL
Size of perforations in, by in.	Basalt . 460 602	
perforations from		w.B.
perforations from ft. to ft.	Basalt 0 696 725	<u> </u>
perforations from ft. to ft.		
(7) SCREENS: Well screen installed? I Vos II No.		
(1) SCREENS: Well screen installed? Yes No Manufacturer's Name		
Type		
Diam. Slot size Set from ft. to ft.		
Diam. Slot size Set from ft. to ft.		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	RECEIVED	
a pump test made? Yes Y No If yes, by whom?	AUC 0 4 1000	
Yield: gal./min. with ft. drawdown after hrs.	AUG 0 4 1980	
" " " " " " " " " " " " " " " " " " "	WATER RESOURCES DEPT	
" " " " " " " " " " " " " " " " " " "	SALEM, OREGON	
Hest 200 gal./min. with 430 ft. drawdown after / hrs.		
Artesian flow g.p.m.		
Temperature of water Depth artesian flow encountered ft.	Work started 7-18 19 80 Completed 7-23	1980
(9) CONSTRUCTION:	Date well drilling machine moved off of well 7-24	1980
Well seal-Material used MM disturbed	Drilling Machine Operator's Certification:	
Well sealed from land surface to ft.	This well was constructed under my direct superv	zision
Diameter of well bore to bottom of sealin.	Materials used and information reported above are true best knowledge and belief.	to my
Diameter of well bore below sealin.	[Signed] Lands To Litel Date 7-24	(1)
Number of sacks of cement used in well seal sacks	(Brining Machine Operator)	19 a
How was cement grout placed?	Drilling Machine Operator's License No	
Activities and the second seco	Water Well Contractor's Certification:	
An All Martin Commencer of the Commencer	This well was drilled under my jurisdiction and this re	nout :-
Was a drive shoe used? ☐ Yes ☐ No Plugs Size: location ft.	true to the best of my knowledge and belief.	POT 12
Did any strata contain unusable water? \(\begin{align*}\text{ Yes } \\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	Name TROY GR /FF/H (Person, firm or corporation) (Type or print	·
Type of water? depth of strata	7 11	
Method of sealing strata off	1 11 10.	1017 01
Was well gravel packed? Yes No Size of gravel:	[Signed] (Water Well Contractor)	
Gravel placed from ft. to ft.	Contractor's License No. 65 Date 7-24	1081

(USE ADDITIO,

NECESSARY)