NOTICE TO WATER WELL INTRACTOR IN The original and first copy of this report. WELL REPORT	
water resources department 1978 STATE OF OREGON State Well No. 4024E-14cc	
SALEM, OREGON 97310 (Please type or print) MANUA (a) a)	
within 30 days from the dete described of well completion.	bove this line)
SALEM, OREGUN 11/2/12	1911 + TE Well Log to 98 poted Hug 4/18
(1) OWNER:	(10) LOCATION OF WELL:
Name W.C. Hendrix	County Morrow Driller's well number 98
Address F.A. Box 15 Board man Oregon	SU! 14 SU' 14 Section 14 T. 4N R. 24 F. W.M.
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner
New Well □ Deepening ☑ Reconditioning □ Abandon □	1250 E. & 1250 N. of S.W. Corner
If abandonment, describe material and procedure in Item 12.	<del>2</del> 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed well.
Rotary Vi Driven C	Depth at which water was first found or igoually /2 -ft.
Cable	Static level 6.5 ft. below land surface. Date 25/79
Dug ☐ Bored ☐ Irrigation ☐ Test Well ☐ Other ☐	Artesian pressure NONE lbs. per square inch. Date Nov. 28/78
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below easing 978"
17 84 Dlam from 5/4 Int. 62:5 tal/the dage	Depth drilled 256. 2ft. Depth of completed well 54/. Left.
ft. to	Formation: Describe color, texture, grain size and structure of materials;
" Diam. from ft. to ft. Gage	and show thickness and nature of each stratum and aquifer penetrated.
PERFORATIONS: Perforated?   Yes   Ye	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	Haid Black Basalt 195.5292. 9. 0
perforations from ft. to ft.	Blue Play Farrer bed 297 440, 395
perforations fromft. toft.	Viscular Bosaltwill 4400 390to
perforations from ft. to ft.	Blue 0/24 5345 65.5
(7) SCREENS: Well screen installed? I Ves IV No.	Here Bieck Basalt 534 541. 65.9
Well screen installed?  Yes  No Manufacturer's Name	
Type Model No.	
Diam. Slot size Set from ft. to ft.	
Diam. Slot size Set from ft. to ft.	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? Yes No If yes, by whom?	
ield: Myox gal./min. with ft. drawdown after //2 hrs.	
" Aprex 800 " 200 @ 4000 ft 1/4 "	
" " "	
Bailer test gal./min. with ft. drawdown after hrs.	
Artesian flow NONF g.p.m.	
Imperature of water of Depth artesian flow encountered NONE ft.	Work started NOCI, 6 19 78 Completed Noci. Z8 19 78
(9) CONSTRUCTION:	Date well drilling machine moved off of well Nac. 28 19 78
Well seal-Material used Pressing Sty Styled	Drilling Machine Operator's Certification:
Well sealed from land surface toft.	This well was constructed under my direct supervision.
Diameter of well bore to bottom of sealin.	Materials used and information reported above are true to my best knowledge and belief.
Diameter of well bore below seal in.	[Signed] Date Nov. 28 19 78
Number of sacks of cement used in well seal sacks	(Drilling Machine Operator)  Drilling Machine Operator's License No.
How was cement grout placed?	Drining Machine Operator's License No.
A STATE OF THE STA	Water Well Contractor's Certification:
	This well was drilled under my jurisdiction and this report is
Was a drive shoe used? [] Yes Mo Plugs Size: location ft.	Name 13 200 M. Trend Drilling Co.
Did any strata contain unusable water?   Yes  No	(Person, firm or corporation) (Type of print)
Type of water? depth of strata	Address P. O. Box 124 Herens ton
Method of sealing strata off	[Signed] Select L. Brown Oregon 9 1838
Was well gravel packed? [ Yes [ No Size of gravel:	(Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No. 5/6 Date Nov. 29, 1975