NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

STATE OF OREGON

MOPPER (db) State Well No. 40 WATER WELL REPORT

State Permit No. 4-3

	The state of the s		
(1) OWNER: WATER RESOURCE	(10) LOCATION OF WELL:		
(1) OWNER: WATER RESOURCES DEP	County Married Driller's well no	umber 7 8	
Address P.O. Box 25 Boarding UREGON	SW 45W 4 Section 14 T4N R. 24 F. W.M.		
19 re gon 9 78/8	Bearing and distance from section or subdivisi	on corner	*******
(2) TYPE OF WORK (check):	1250 E. & 1250 N. of	Sin Com	
New Well 💢 Deepening 🗌 Reconditioning 🗀 Abandon 🗔	M Sec. 14		7) Guge
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	1 mm 0		
Rotary Driven Domestic Industrial Municipal	Depth at which water was first found ft.		
The state of the s	Static level ft. below land s	73	19.7/T
Dug Bored Irrigation Test Well Other	Artesian pressure / blbs. per squar	e inch. Date	143
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well h	8" to 18.	5%.6
10 "Diam. from 11 of ft. to 19 of ft. Gage 250	Depth drilled 85. oft. Depth of completed well / 85. oft.		
ft. Gage ft. Gage			it.
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and show thickness and nature of each stratum	m and aquifer ne	netrated
PERFORATIONS: Perforated? \(\text{Ves} \) \(\text{Ves} \)	with at least one entry for each change of format position of Static Water Level and indicate prin	tion. Report each o	hange in
Type of perforator used Perforated? Yes No.		cipal water-bearing	ig strata.
	MATERIAL	From To	SWL
Size of perforations in. by in,	Hard Tight Silt	0,0 3.0	
perforations from	Highly Fractured Basalt	3.2 11.2	20
perforations fromft. toft.	Had Black Bond	200 000	8 . =
perforations from ft. to ft.	Soffer Brown Basalt	36.2 59.2	<u> </u>
(7) SCREENS: Well screen installed? Yes No	Hard Grey Class	127.0 140.0	£
Manufacturer's Name	Med Sext Black Basalt	140.2 1775	·
Type	Hard Block Basalt	1725 1853	8.0
Diam. Slot size Set from ft. to ft.		///	
Diam. Slot size Set from ft. to ft.			
(8) WELL TESTS: Drawdown is amount water level is			
Was a pump test made? Yes No If yes, by whom?			
7:4-7			
Yield 7 / 85 gal./min. with ft. drawdown after hrs.			-
7130 + " 70 " 2 "			
" " " " " " " " " " " " " " " " " " " "			
Bailer test gal./min. with ft. drawdown after hrs.			
Artesian flow NONE g.p.m.			
iperature of water. 5 Depth artesian flow encountered Nary	Work started July 29 1978 Complete	Aug.3	19 78
(9) CONSTRUCTION:	Date well drilling machine moved off of well	my 4	19 7 5
Well seal—Material used Caman & Crouk	Drilling Machine Operator's Certification:		
Well sealed from land surface to 19.6 ft.	This well was constructed under my	direct super	vision.
Diameter of well bore to bottom of sealin.	Materials used and information reported above are true to my best knowledge and belief.		
Diameter of well bore below seal in.	[Signed] Date , 19		
Number of sacks of cement used in well seal sacks	, , , , , ,		
How was cement grout placed?	Drilling Machine Operator's License No.		
Granting Carry Dichard	Water Well Contractor's Certification:		
1 + to Annular space dit Plus.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.		
Was a drive shoe used? Yes No Plugs Size: location ft.	Name Brewn Brown Drilling Co		
Did any strata contain unusable water? Tyes The	(Person, firm or corporation)	(Type or prin	t)
Type of water? depth of strata	Address P.O. Box 124 He	miston	Ore
Method of sealing strata off	[Signed] Jahn J. Br.		971
Was well gravel packed? [] Yes No Size of gravel:	(Water Well Contra	etor)	0
Gravel placed from ft. to ft.	Contractor's License No. 516 Date	4.4.4	, 1978