NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

STATE OF OREGON

(Please type or print) STATE ENGINEER No. STATE ENGINEER, SALEM, OREGON 97310

(Please type or print) STATE ENGINEER

within 30 days from the data
of well completion.

(Please type or print) STATE ENGINEER

of well completion.

100,000		
(1) OWNER: CORPS OF ENGINEERS BOARDMAN PARK	(10) LOCATION OF WELL: County MORROW Driller's well num	mber 5422
DIAZ LAS Con Court Repre		R. 2 5 E. W.M.
WALLA WALLA, WASH	Bearing and distance from section or subdivisio	
(2) TYPE OF WORK (check):	Dearing and distance 2002	· · · · · · · · · · · · · · · · · · ·
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐		
If abandonment, describe material and procedure in Item 12.	(44) TYADED I EXCEL. Completed was	.11
	(11) WATER LEVEL: Completed we	71.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	23 n.
Rotary Driven Domestic Industrial Municipal Cable Jetted	Static level ft. below land st	irface. Date /0/3/72
Dug Bored I Irrigation Test Well Other	Artesian pressure lbs. per square	inch. Date
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well b	elow essing
/6 " Diam. from 0 ft. to 22 ft. Gage 375	· · · · · · · · · · · · · · · · · · ·	
12-" Diam from 0 ft. to 35 ft. Gage 1375		
// " Diam. from 31 ft. to 35 ft. Gage , 250	Formation: Describe color, texture, grain size a and show thickness and nature of each stratun	n and aquifer penetrated,
DALLES AND	with at least one entry for each change of format	ion. Report each change in
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate princ	npal water-bearing strata.
Type of perforator used	MATERIAL	From To SWL
Size of perforations in, by in.	PIT	0 4
perforations fromft. toft.	5147	46
perforations from ft. to ft.	SAND AND GRAVEL	6 23
perforations from ft. to ft.	CLEAN GRAVEL	23 25
perforations from	CLEAN LIGHT BROWN	
(7) SCREENS: Well screen installed? Yes I No	SAND SOME GRAVEL	25 45
Mailulacturel & Maile	SANO AND GRAVEL	45 50
THE STAINLESS STEEL Model No.	19 T 29 T 29 T 20 T 20 T 20 T 20 T 20 T 2	
Diam. 12 Slot size 40 Set from 35 ft. to 50 ft.		
Diam. Slot size Set from ft. to ft.		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		
Was a pump test made? Yes \(\subseteq \text{No If yes, by whom?} \)	2	
Yield: 400 gal./min. with & ft. drawdown after 48 hrs.		
500 " 8 " 72 "		
	- <u></u>	
Bailer test gal./min. with ft. drawdown after hrs.		
Artesian flow g.p.m.		
perature of water 6/Depth artesian flow encountered ft.	Work started 5EPT, 1319 72 Complete	
(0) CONSTRUCTION.	Date well drilling machine moved off of well	017-10 1977
(9) CONSTRUCTION: Well seal_Material used CEMENT GROUT	Drilling Machine Operator's Certification:	
Well seal—Material used	This well was constructed under my	direct supervision.
Well sealed from land surface toft.	Materials used and information reported	above are true to my
Diameter of well bore to bottom of sealin.	best knowledge and belief.	- 07/2 77
Diameter of well bore below sealin.	[Signed] (Drilling Machine Operator)	Date 007/2, 19 77
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No.	5/
Number of sacks of bentonite used in well seal sacks		
Brand name of bentonite	Water Well Contractor's Certification:	<u>-</u>
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisd	iction and this report is
of waterlbs./100 gals.	true to the best of my knowledge and be	lief.
Was a drive shoe used? Yes No Plugs Size: location ft.	Name .1.1.	eiring co
Did any strata contain unusable water? Yes No	(Person, firm or corporation)	UE PETIAND
Type of water? depth of strata	Address 8// Colored	
Method of sealing strata off	[Signed] Sabert J. Sh	asser
Was well gravel packed? Yes No Size of gravel:	(Water Well Cont	
Gravel placed from ft. toft.	Contractor's License No Date	OCT 12, 197

NOTICE TO WATER WELL CONTRACTOR The original and first copy
of this report are to be
filed with the

ο.	4N	25	E	****	8	
u.						•

STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date
of well completion.

(1) OWNER: CORPS OF ENGINEERS	(10) LOCATION OF WELL:	- 12-1	
Name BOARDMAN PARK	County MORROW Driller's well number 5 4111		
Address BIRG 602 CITY COUNTY FIRPOR	SE 1 NW 1 Section & T. 4N F	25 W.M.	
WALLA WALLA WASH.	Bearing and distance from section or subdivision	corner	
(2) TYPE OF WORK (check):			
New Well Deepening Reconditioning Abandon			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed we	11.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	2.5 ft.	
Rotary Driven Domestic Dindustrial Municipal D	Static level \$ ft. below land su	rface. Date 10/3/12	
Cable Jetted Dug Bored D Irrigation Test Well Dother D	Artesian pressure lbs. per square	inch. Date	
CASING INSTALLED: Threaded Welded	(10) WITH FOC		
16" Diam. from 6 ft. to 22 ft. Gage 37.5	(12) WELL LOG: Diameter of well below casing		
/2 Diam from O ft. to 30 ft. Gage 375	Depth drilled 50 ft. Depth of complet	ed well SC ft.	
11 "Diam from 26 ft to 30 ft Gage -250	Formation: Describe color, texture, grain size an and show thickness and nature of each stratum		
Diant. Home	with at least one entry for each change of formation	on. Report each change in	
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate princi	pal water-bearing strata.	
Type of perforator used	MATERIAL	From To SWL	
Size of perforations in. by in.	PIT	04	
perforations fromft. toft.	5157	46	
perforations fromft. toft.	SANDAND GRAVEL	6 23	
perforations fromft. toft.	CIEAN GRAVEL	23 25	
periorations port	CLEAN LIGHT BROWD		
(7) SCREENS: Well screen installed? X Yes No	SAND SOME GRAVEL	25 45	
Manufacturer's Name UOP JOHNSON	SAND AND GRAVEL	45 50	
Type JT/A/A'LESS STEELModel No.			
Diam. 12 Slot size 40 Set from 30 ft. to 570 ft.			
Diam. Slot size Set from ft. to ft.			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level			
Was a pump test made? Yes \(\subseteq No \) If yes, by whom? \(\subseteq 776.755\) Ek			
Yield: 400 gal./min. with 6 ft. drawdown after 48 hrs.			
500 " 8 " 72"			
" " "	The state of the second of the		
Bailer test gal./min. with ft. drawdown after hrs.	The second secon		
Arresian now g.p.m. Amperature of water 6/Depth artesian flow encounteredft.	Work started SEPT / 519 72 Complete	OCT 10 1972	
	Date well drilling machine moved off of well	OCT 10 1972	
(9) CONSTRUCTION: Well seal—Material used CEMENT GROUT	Drilling Machine Operator's Certification:		
at .	This well was constructed under my	direct supervision.	
Well sealed from land surface toft.	Materials used and information reported	above are true to my	
Diameter of well bore to bottom of sealin.	best knowledge and belief.	Date Oc7 /21972	
Diameter of well bore below sealin.	[Signed] (Drilling Machine Operator))ate	
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No	_57	
Number of sacks of bentonite used in well seal sacks	Stands 1240min 4pp		
Brand name of bentonite	Water Well Contractor's Certification:		
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdic	etion and this report is	
of waterlbs./100 gals.	with the mine steps of the steps with steps with steps with the steps of the steps with the step w		
Was a drive shoe used? Yes No Plugs Size: location ft.	Name KJSTRASSER DRILLING CO. (Person, firm or corporation) (Days, or print)		
Did any strata contain unusable water? Tyes No	Address 8/10 SE SUNSET LAK	IE PORTANDO	
Type of water? depth of strata	DOD VY TI		
Method of sealing strata off	[Signed] (Water Well Contra	Maria Company	
Was well gravel packed? ☐ Yes No Size of gravel:		OCT /2 1972	
Gravel placed from ft. to ft.	Contractor's License No Date		