NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion. STATE OF OREGON MORR 712
State Well No. 40/25E-9ca
(Phile Pri 4970t) MORR 712
State Permit No.

THE RESOURCES DEPT				
(1) OWNER:	FA9NLOCATION OF WELL:			
Name Homer G. Prichard	County Merrows Driller's well n		a 1	
		umber	12	
Address Rt. / Box 77 Boarding	SE 4 SW4 Section 9 T. 4N	R. Z.	E	W.M.
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivis	ion corner		
	Aprix 135'N. & 2225'W	. 0/5	,E	COKING
New Well Deepening Reconditioning Abandon If shandarment describe metapial and massadams in Mars. 18	- of Sec. 9			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	rell.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	0.=		ft
Rotary Driven Domestic Industrial Municipal	Static level 66. tt. below land	surface. I	Date . Isa	1.3/2
Dug Bored I Irrigation Test Well Other	Andreis			174
enjur comented Inside of onig, 121kgs	- WENE		<u> </u>	<u> 14 3/7</u> 0
CASING INSTALLED: Threaded Welded	(12) WELL LOG: C''+0267.	helow one	5	30.
/ C ft. to ft. Gage 2.55	Depth drilled 560.5 ft. Depth of compl	leted well	~ A	0. 2 ft.
ft. to ft. Gage				
	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,			
PERFORATIONS: Perforated? \(\sigma\) Ves \(\overline{\sigma}'\) No	with at least one entry for each change of forma position of Static Water Level and indicate prin	tion. Repo	rt each d	change in
restorated. If tes a no.	position of Static Water Level and indicate prin	icipai wat	er-pearir	ig strata.
Type of perforator used	MATERIAL	From	То	SWL
Size of perforations in. by in.	Med. Hard Grey Besolt	30.0	62.0	
perforations from ft. to ft.	15 Hard Black Bassit	6.2. C	98.5	70,2
perforations from ft. to ft.	Blue clay	98.0	135.5	66.2
perforations from ft. to ft.	Blackviscular Bosalt	1.35 5	60.5	2
(7) SCREENS: Well screen installed? Ves. Vi No.	Hard Block Bosolt	1600	295.	
Well screen installed? Wes No Manufacturer's Name	Blue clay		420.	<u> </u>
Type Model No	Blue clay with various	420.5		
Diam. Slot size Set from ft. to ft.	Types & Sizes ROCK	 	-	
Diam. Slot size Set from ft. to ft.	frigments.	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	783	
16.	V13 Elilar 13050 17	#85 ª	590.	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Die dil man min			,,,
Was a pump test made? Yes No If yes, by whom?	This well wis origi	16/4	dri	1/20
	Dy 17/11 Son 47-11/16/1	20:	0	
Yield: 4,7 185 gal./min. with ft. drawdown after hrs.	1/2 /2 /1/ 0 /70	-30,		
17 1X. 300 GFM. 100 pt. " 1/2 Hrs.		 		
11 .11 11	7 .	-		
Bailer test gal./min. with ft. drawdown after hrs.				
Artesian flow NINE g.p.m.				
perature of water 54 Depth artesian flow encountered 1700 Eft.	Work started June 19 1978 Complete	1./.	. 2	عرّ ،،
		30,7476	/ 2 -	19/0
(9) CONSTRUCTION:	Date well drilling machine moved off of well	414-	<u> </u>	19 / 8
Well seal—Material used Californ's Gract	Drilling Machine Operator's Certification:			
Well sealed from land surface toft.	This well was constructed under my Materials used and information reported	direct	super	vision.
Diameter of well bore to bottom of seal 10' Cos. ins. de	best knowledge and belief.	above a	re true	to my
Diameter of well bore below sealin_erriq.12 "C15,	[Signed]	Date .i.	143	1978
Number of sacks of cement used in well seal	(Drilling Machine Operator)	110	-5	, 104
How was cement grout placed? Well Mixed Paure	Drilling Machine Operator's License No.		>->	
10 5106 10 W,74 2 p. por to 25. 50	Water Well Contractor's Certification:			
TILIO Casing of y dottoon pushed	ł			
side a plughoner lattom of casing.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.			
Was a drive shoe used? Yes No Plugs Size: location ft.	Name Brian & Brigin Drilling Co.			
Did any strata contain unusable water? Yes No	(Person, firm or corporation)	(Typ	e or prin	t)
Type of water? depth of strata	Address . B. Pox 124, Hermisi	81,6	reg	0 +1
Method of sealing strata off	[Signed] Dalm I Bras	4 pmgs - 2	, 19	1838
Was well gravel packed? ☐ Yes Y No Size of gravel:	[Signed] (Water Well Contr	actor)	••••••	
Gravel placed fromft. toft.	Contractor's License No. 5/1. Date	Ma	. 3	10 70
	, Date			, LU. J