NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

## WATER WELL REP

STATE ENGINEER, SALEM, OREGON 87310 within 30 days from the date

STATE OF OREGON  $\overline{0V}$  1 9 1975

TATE OF OREGONOV 1 9 1975			44-23E-10
(Please typ WATER RESOURCES	DEPT.	Darmit N	Vo.
	s State	T CITIE I	10

(Do not write above the ALEM. OREGON of well completion. (10) LOCATION OF WELL: (1) OWNER: Driller's well number Homer G. Prichard County Morrow Name Rt.1 Box 77 SW 14 SW 14 Section 10 T4N W.M. R.25E Address Boardman. Oregon Bearing and distance from section or subdivision corner (2) TYPE OF WORK (check): 1280ft N of the SW sec. corner and 150ft E. of sec. line New Well □ Deepening 1 Reconditioning [ Abandon | If abandonment, describe material and procedure in Item 12. (11) WATER LEVEL: Completed well. (3) TYPE OF WELL: (4) PROPOSED USE (check): Depth at which water was first found Rotary Driven 🔲 ft. below land surface. Date 5 Nov Domestic | Industrial | Municipal | Static level Cable Jetted [ Irrigation X Test Well Other Bored [7] Artesian pressure lbs. per square inch. Date CASING INSTALLED: (12) WELL LOG: Threaded | Welded | Diameter of well below casing 12-10-8" 10 "Diam from 0 ft. to 187 ft. Gage ... ft. Depth of completed well Depth drilled 502 8 "Diam from 310 ft. to 430 ft. Gage • 188 Formation: Describe color, texture, grain size and structure of materials; " Diam. from ...... ft. to ...... ft. Gage ..... and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata. PERFORATIONS: Perforated? XYes | No. Torch SWT. MATERIAL From pe of perforator used 72 Basalt black WB 80 40 in. by Size of perforations 80 125 Basalt gray 125 130 Basalt black WB ..... perforations from ...... ft. to ..... ft. 130 135 Claystone gray perforations from ...... ft. to ...... ft. 135 Clay blue-green 150 (7) SCREENS: 150 183 Claystone blue-green Well screen installed? ☐ Yes 🛛 No 200 183 Manufacturer's Name ..... Basalt black 200 322 Basalt gray ...... Model No. ...... 322 327 Diam. Slot size Set from ft. to ft. Claystone gray Diam. ...... Slot size ...... Set from ..... ft. to ..... ft. 327 350 Clay green 350 433 Claystone green WB Drawdown is amount water level is lowered below static level (8) WELL TESTS: Basalt black visicular 433 502 Was a pump test made? 

Yes 
No If yes, by whom? gal./min. with ft. drawdown after hrs. fir test 200 gal. min. @ 500ft. gal./min. with ft. drawdown after Bailer test Artesian flow g.p.m. 1975 Completed 15 NOV. Work started 31 Oct 1975 Depth artesian flow encountered ...... ft. nperature of water Date well drilling machine moved off of well 19 7 5 (9) CONSTRUCTION: Drilling Machine Operator's Certification: Well seal-Material used ..... This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowled for and belief. Well sealed from land surface to \_\_\_\_\_\_ ft. [Signed] Jones Mechine Operator) Date 17. No.y 19.75 Diameter of well bore to bottom of seal ..... in. Diameter of well bore below seal ..... in. Number of sacks of cement used in well seal ...... Drilling Machine Operator's License No. .. 28 Number of sacks of bentonite used in well seal \_\_\_\_\_ sacks Brand name of bentonite ..... Water Well Contractor's Certification: Number of pounds of bentonite per 100 gallons This well was drilled under my jurisdiction and this report is ..... lbs./100 gals. true to the best of my knowledge and belief. Was a drive shoe used? 

Yes 

No Plugs ....... Size: location ...... ft. Name Richard J. Murray (Type or print) Did any strata contain unusable water? 

Yes 
No Address 3712 W 8th The Dalles, Oregon depth of strata Type of water? Method of sealing strata off Was well gravel packed? ☐ Yes ☐ No Size of gravel: ..... Contractor's License No. 606... Date 1.7 Mov......, 19.75 Gravel placed from ...... ft. to ..... ft.