NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

WATER WELL REPORT GEIVE STATE OF OREGON JUN 1 3 1973 state Well No.

~				055		00010-
TATE	ENGINE	er, s	ALEM	, OREC	ATO P	91340
	within 20	down	from	the dat	~~~	-

(Please type or pSTATE ENGINE THE Permit No. ...

of wen completion. Plower 18 / Go not write as	WE WAS BELLEM. OREGON					
(1) OWNER:	(10) LOCATION OF WELL:					
Name Port of Morraul Comm,	County Morrow Driller's well nu	mber 5	4			
Address City Hall, Boardman, oregon 97818	NE 1/4 NW1/4 Section 10 T. 4N	r. 25	E.	W.M.		
(9) TYPE OF WORK (shock).	Bearing and distance from section or subdivision					
(2) TYPE OF WORK (check):	270 due North of S.W.			fthe		
New Well	NE 14 of the W.W. 14 sec.	<u>~f.Sec</u>	2,10	<u> </u>		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed we	еЙ.				
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 7, =			ft.		
Rotary Driven Domestic Dindustrial Municipal Domestic Dindustrial	Static level 5, 5 ft. below land st	urface. Da	ate J 4	2011/		
Cable Jetted Irrigation Test Well Other	Artesian pressure NONE lbs. per square	e inch. Da	ate Jur	2 11/2		
CASING INSTALLED: Threaded Welded			wa	< 15 W		
Jb "Diam. from O. ft. to 47.5 ft. Gage) 50 will	Depth drilled 46.0 Chiameter of well b	eted well	94/6	. <u>S</u> ft.		
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size a		re of m	aterials:		
ft. toft. Gage	and show thickness and nature of each stratum and aquifer penetrated,					
PERFORATIONS: Perforated? Y Yes [] No.	with at least one entry for each change of format position of Static Water Level and indicate princ					
Type of perforator used Mills Knife	MATERIAL	From	то	SWL		
Size of perforations $\frac{1}{16}$ in. by $\frac{3}{16}$ in.	Hard sandy Silt, Tops oil	0.5	20			
240 perforations from 35.5 ft. to 42.5 ft.	Sand avove / Capples 5	20				
perforations fromft. toft.	Boulder 5	2	8,5	7.0		
perforations fromft. toft.	Course Ind & grave/	28.5 4	12.5	7,5		
(E) CODEENC	med grained send	4254	14.5	5.5		
(7) SCREENS: Well screen installed? ☐ Yes ▼ No	Boulder, sygrounded	44.0				
Manufacturer's Name	by Med. grain brown sand		45.2	5,2		
Type Model No.	Med. grain prown Sond.	45.5	78.	<u> 5. 5</u>		
Diam. Slot size Set from ft. to ft. Diam. Slot size Set from ft. to ft.	Constant to the second	 	-+			
December 100 miles	Comented hole back					
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Tron 40 10 76. 2					
Was a pump test made? \(\text{Yes} \) Yes \(\text{P} \) No If yes, by whom of \(\text{Pas(o.} \)	to Prevent numbina					
Yield: gal./min. with ft. drawdown after hrs.	sand.					
, m						
" " " "	14					
Bailer test 60 gal./min. with 7.5 ft. drawdown after //2 hrs.			\longrightarrow			
			\longrightarrow			
	72		\longrightarrow			
cerature of water 55 Depth artesian flow encountered NON Est.	Work started /// 19/3 Complete	dun	e 11	19/3		
(9) CONSTRUCTION:	Date well drilling machine moved off of well	une	_//_	<u>19</u> プゴ		
Well seal-Material used Bon ton, te	Drilling Machine Operator's Certification: This well was constructed under my	direct	cunari	vicion		
Well sealed from land surface toft.	Materials used and information reported	above ar	e true	to my		
Diameter of well bore to bottom of seal in.	best knowledge and belief.	Λ.		~ ~		
Diameter of well bore below seal	[Signed] (Drilling Machine Operator)	Date Ju	re)	, 19. / 5		
Number of sacks of cement used in well sealsacks	Drilling Machine Operator's License No	481				
Number of sacks of bentonite used in well sealsacks Brand name of bentonite						
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:					
of water NOT Metered, well mixed 1bs./100 gals.	This well was drilled under my jurisdi true to the best of my knowledge and beli		this re	eport is		
Was a drive shoe used? Yes No Plugs	Name B. & B. Drilling C	5				
Did any strata contain unusable water? Yes No	(Person, firm or corporation)	Type	e or prin	.t)		
Type of water? depth of strata	Address P.O. L. 30x 129 Hermi	Ston,	Ore	; 4783		
Method of sealing strata off	[Signed] James L. Bro	run				
Was well gravel packed? ☐ Yes No Size of gravel:	(Water Well Contractor's License No. 5 12 Date Of	actor)	, ,	7 <i>2</i>		
CONTROL MICROSIA FOR THE SELECTION OF TH	LI COURTE DOTORE LIGORES NO. 3 / 4 13045 \ /4			10 / 7		