NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER WELL REPORT EIVED

STATE OF OREGON AUG 9 1982

)	State	Well	No.

WATER RESOURCES	DEPARTMENT
SALEM, OREC	ON 97310
within 30 days fr	om the date
	1 diam/

Gravel placed from ft. to ft.

(Please type of WATER RESOURCES DEPT Permit No. (Do not write above this line LEM, OREGON

		_	
(1) OWNER;	(10) LOCATION OF WELL:	_	
Name Derry Downey	County Morrow Driller's well number 226	, ——	
Address BOX 64	14 14 Section 14 T. 4N R.25 E W.	<u>M.</u>	
Boardman, ORE 97814	Bearing and distance from section or subdivision corner		
(2) TYPE OF WORK (check):		_	
New Well 📐 Deepening 🗌 Reconditioning 🗍 Abandon 📙			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found / 2 6 ft.		
Rotary Driven Domestic Industrial Municipal	Static level 46 ft. below land surface. Date		
Cable	Artesian pressure lbs. per square inch. Date		
		_	
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing	(2)	
8 " Diam. from + 1 ft. to - 3.5 ft. Gage	Depth drilled 3/0 ft. Depth of completed well 5/0	ft.	
" Diam. from	Formation: Describe color, texture, grain size and structure of materia	als;	
" Diam. from ft. to ft. Gage	and show thickness and nature of each stratum and aquifer penetrat with at least one entry for each change of formation. Report each change	e in	
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate principal water-bearing stra	ata.	
pe of perforator used	MATERIAL From To SWI	L	
Size of perforations in. by in.	Sand 0 25 0		
perforations from ft. to ft.	Brown Basalt 25 29 0		
perforations from ft. to ft.	Black Basaft 29 82 0		
perforations from ft. to ft.	Gray Basalt 82 95 0		
	Visicular Boself with 95 126 0		
(7) SCREENS: Well screen installed? Tyes No	VISIT 400 Puso 14 126 175 4	6	
Manufacturer's Name	Round Basalt 145 148	<u> </u>	
Diam. Slot size Set from ft. to ft.	Plack 13050 14 145 178		
Diam. Slot size Set from ft. to ft.	Hora R 50 178 265		
	Wisitulan Rasalt 265 276		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Blue Clas 276290		
Was a pump test made? Yes No If yes, by whom?	VISicular Basalt 290 310		
Yield: gal./min. with ft. drawdown after hrs.			
ir test " 300 G"PM "			
Bailer test gal./min. with ft. drawdown after hrs.			
3445			
Artesian flow g.p.m.	Work started 19 Quile 19 & 2 Completed 26 Quile 19	8	
perature of water Depth artesian flow encountered ft.	Work Boards Tracky		
(9) CONSTRUCTION:	Date well drilling machine moved off of well 26 July 19	<u>~</u>	
Well seal-Material used Cement	Drilling Machine Operator's Certification:	~ ~	
Well sealed from land surface to	This well was constructed under my direct supervision Materials used and information reported above are true to	nn. my	
Diameter of well bore to bottom of seal in. 25	best knowledge and belief.		
Diameter of well bore below seal	[Signed Down Date 26 1944, 19.4	8.2	
Number of sacks of cement used in well sealsacks	Drilling Machine Operator's License No.		
How was cement grout placed? Tremaicd	Drining Wathine Operator's License No.		
	Water Well Contractor's Certification:		
	This well was drilled under my jurisdiction and this report	t is	
	true to the best of my knowledge and belief.		
Was a drive shoe used? Yes □ No Plugs Size: location ft.	Name Brown & Brown Urillian	ĝ	
Did any strata contain unusable water? Yes	Address O BOX 124 Merson S	テラ	
Type of water? depth of strata	Address Ook Jelly		
Method of sealing strata off	[Signed]		
Was well gravel packed? [Yes No Size of gravel:	(Water Well Contractor)	_	

Contractor's License No. 728 Date 26 June