

NOTICE TO WATER WELL CONTRACTOR
 The original and first copy of this report are to be filed with the
 WATER RESOURCES DEPARTMENT
 SALEM, OREGON 97330
 within 30 days from the date
 of well completion.

RECEIVED
RECEIVED
RECEIVED
 WATER WELL PERMITS
 STATE OF OREGON
 (Please type or print)
 FEB 27 1978
 MAR 21 1978 (Do not write above this line)
 WATER RESOURCES DEPT.
 SALEM, OREGON

State Well No. 4N/25E-14bc
 State Permit No. MORR 791

(1) OWNER: WATER RESOURCES DEPT.
 Name Charles Kyd SALEM, OREGON
 Address P.O. Box 199
Boardman, Oregon 97818

(2) TYPE OF WORK (check)
 New Well Deepening Reconditioning Abandon
 If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
 Rotary Cable Dug Driven Jetted Bored
 (4) PROPOSED USE (check):
 Domestic Industrial Municipal Irrigation Test Well Other

CASING INSTALLED:
 6" Diam. from 0 ft. to 47 ft. Gage .250
 " Diam. from ft. to ft. Gage
 " Diam. from ft. to ft. Gage

(5) PERFORATIONS:
 Perforated? Yes No
 Type of perforator used
 Size of perforations in. by in.
 perforations from ft. to ft.
 perforations from ft. to ft.
 perforations from ft. to ft.

(7) SCREENS:
 Well screen installed? Yes No
 Manufacturer's Name
 Type Model No.
 Diam. Slot size Set from ft. to ft.
 Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:
 Drawdown is amount water level is lowered below static level
 Was a pump test made? Yes No If yes, by whom?
 Yield: gal./min. with ft. drawdown after hrs.
 " " " " " "
 " " " " " "
 Pump test 30 gal./min. with 38 ft. drawdown after 1 hrs.
 Artesian flow g.p.m.
 Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:
 Well seal—Material used Cement
 Well sealed from land surface to 47 ft.
 Diameter of well bore to bottom of seal 9 in.
 Diameter of well bore below seal 6 in.
 Number of sacks of cement used in well seal 12 sacks
 How was cement grout placed?
 Was a drive shoe used? Yes No Plugs Size: location ft.
 Did any strata contain unusable water? Yes No
 Type of water? depth of strata
 Method of sealing strata off
 Was well gravel packed? Yes No Size of gravel:
 Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
 County Morrow Driller's well number
SW 1/4 NW 1/4 Section 14 T. 47N. R. 5E. W.M.
 Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
 Depth at which water was first found 64 ft.
 Static level 66 ft. below land surface. Date 2-13-78
 Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 6"
 Depth drilled 107 ft. Depth of completed well 107 ft.
 Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Sand	0	30	
Rock, brown	30	42	
Basalt black	42	63	
Rock, black/brown claystone	63	70	
Basalt, black	70	88	
Rock, brown	88	96	W.B.
Rock, brown w/ grey claystone	96	102	W.B.
Claystone, brown	102	107	

Work started 2-10 1978 Completed 2-13 1978
 Date well drilling machine moved off of well 2-13 1978

Drilling Machine Operator's Certification:
 This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
 [Signed] Thomas J. DeLaine Date 2-13, 1978
 (Drilling Machine Operator)
 Drilling Machine Operator's License No. 1210

Water Well Contractor's Certification:
 This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
 Name TRAY GRIFFIN
 (Person, firm or corporation) (Type or print)
 Address 900 HERMISTON AVE, HERMISTON, OREGON
 [Signed] Tray Griffin
 (Water Well Contractor)
 Contractor's License No. 65 Date 2-13, 1978