NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

filed with the

WATER WELL REPORTE CEIVED
STATE OF OREGON
STAT

(Please type or print)

MAY 12 1976 State Permit No. ... (Do not write above this line) ER RESOURCES DEPT. noz

(1) OWNER:	(10) LOCATION OF WELL:
Name Kleser Springs Estates	County Morrow Driller's well number
Address P.O. Boy 2013	10 11 17 1100
Boardman Oregon 47818	
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner
New Well Deepening □ Reconditioning □ Abandon □	
If abandonment, describe material and procedure in Item 12.	(11) YEAR MED T ENVIOLE OF 1 / 1 / 1
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed well.
Rotary M Driven D	Depth at which water was first found 12 ft.
Cable	Static level 73 ft. below land surface. Date 4/3:/16
Dug Bored Irrigation Test Well Other	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded Welded 17.	(12) WELL LOG: Diameter of well below casing
	Depth drilled 195 ft. Depth of completed well 195 ft.
	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,
PERFORATIONS: Perforated? Yes No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
ype of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	Topsvil 0 3
perforations from ft. to ft.	Sand, gray 3 12
perforations from ft. to ft.	Sand, Walle bearing 12 22
perforations from ft. to ft.	Rock, hard, light brown 22 41
(7) SCREENS: Well screen installed? Ves D'No	Basact 41 47
(1) SCREENS: Well screen installed? Yes SCNo Manufacturer's Name	Basser, Kard, gray 77 96
Type Model No.	Claystone, brown 96 112 W.B
Diam. Slot size Set from ft. to ft.	Rock Illack + blue clayation 112 180 w.B.
Diam. Slot size Set from ft. to ft.	Basalr, hard, gray 180 185 Basalr, broken, gray 185 195 W.B.
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Basaer, broken; grey 185 195 W.B.
Was a pump test made? Yes No If yes, by whom?	
Yield: gal./min. with ft. drawdown after hrs.	
" " "	
" " "	
Bailer test 500 gal./min. with 77 ft. drawdown after 2 hrs.	
Artecion flow	
perature of water Depth artesian flow encountered ft.	Work started 4-26 1976 Completed 4-30 1976
(9) CONSTRUCTION:	Date well drilling machine moved off of well 4-30 1976
Well seal-Material used Cenunt Grout	Drilling Machine Operator's Certification:
Well sealed from land surface to 1/2 ft.	This well was constructed under my direct supervision. Materials used and information reported above are true to my
Diameter of well bore to bottom of sealin.	best knowledge and belief.
Diameter of well bore below seal in.	[Signed] Janus Tofeiteh Date 3-10 1976
Number of sacks of cement used in well sealsacks	(Drilling Machine Operator) Drilling Machine Operator's License No.
Number of sacks of bentonite used in well seal sacks	Drining Machine Operator's License No.
Brand name of bentonite	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdiction and this report is
of waterlbs./100 gals.	true to the best of my knowledge and belief.
Was a drive shoe used? ☐ Yes ☑ No Plugs Size: location ft. Did any strata contain unusable water? ☒ Yes ☐ No	Name TROY GRIFFIH (Person, firm or corporation) (Type or print)
Type of water? Sandy depth of strata 12622	Address GOO HERMISTON AVE, HERMISTON ORE
Method of sealing strata off (asing 7 Cervent Was well gravel packed? □ Yes ▼No Size of gravel:	[Signed] (Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No. 65 Date 5-10 , 1976
10. 10	Contractor's Intense No