NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be

STATE ENGINEER, SALEM, OREGON 9731 within 30 days from the date of well completion.

filed with the

WATER WELL REPORT CEIVEU STATE OF OREGON OCT 4 1973 State Well No. 554/3

(Please type or print) STATE ENGINEER State Permit No. 14931
(Do not write above this line SALEM, OREGON 50

(1) OWNER:	(10) LOCATION OF WELL:
NameCLARENCEW, RUDDELL	County Marrio Driller's well number
Address 105 E. ST. Hermister One	5. W 1/4 5 VV 1/4 Section 19 T. UN R. 27 E W.M.
97838	Bearing and distance from section or subdivision corner 1200 N
(2) TYPE OF WORK (check):	+7,920 F of The SIN C.
New Well	of Lea. 19
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 50 . ft.
	7/12/-
Cable  Jetted  Domestic  Middistrial  Midificipal	Static level 5 ft. below land surface. Date 3//1/
Dug 🗌 Bored 🗍 Irrigation 💆 Test Well 🗌 Other 🗍	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded   Welded	(12) WELL LOG: Diameter of well below casing 2000
The "Diam from the ft. to ft. Gage ft. Gage	Depth drilled $1/2$ ft. Depth of completed well $1/2$ ft.
"Diam. from	Formation: Describe color, texture, grain size and structure of materials;
	and show thickness and nature of each stratum and aquifer penetrated,
PERFORATIONS: 2 Perforated? Yest 17 No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
pe of perforator used Mills Miff	MATERIAL From To SWL
Size of perforations /// in. by // in.	Corse South 0 6/
772 perforations from 79 ft. to 105 ft.	Clay from
perforations fromft. toft.	Con 2 1 1 6/8/
perforations from ft. to ft.	Clay Len 3
(7) SCREENS: Well screen installed?   Yes Wood No.	Coffee for 8/10/
	(lay Dark 10/ 112
Manufacturer's Name	
Type	
Diam.       Slot size       Set from       ft. to       ft.         Diam.       Slot size       Set from       ft. to       ft.	
Diant Slot size Set from 1t. to	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made?  Yes No If yes, by whom?	
Yield: Fal /200gal./min. with ft. drawdown after hrs.	
" " "	
" " "	
Bailer test gal./min. with ft. drawdown after hrs.	
	10/0 100
perature of water Depth artesian flow encountered ft.	Work started / 3 / 9 19/2 Completed 19
(9) CONSTRUCTION:	Date well drilling machine moved off of well 4/23 1973
Well seal—Material used Comment	Drilling Machine Operator's Certification:
Well sealed from land surface toft.	This well was constructed under my direct supervision.  Materials used and information reported above are true to my
Diameter of well bore to bottom of sealin.	best knowledge and belief.
Diameter of well bore below sealin,	[Signed] 12 1 2 1 Date 9/24, 1973
Number of sacks of cement used in well sealsacks	(Drilling Machine Operator)
Number of sacks of bentonite used in well sealsacks	Drilling Machine Operator's License No.
Brand name of bentonite Landauren	Window Will Clauder starts Claudifications
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:
of water lbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was a drive shoe used? Yes 🗆 No Plugs Size: location ft.	
Did any strata contain unusable water?   Yes   No	Name (Person firm or corporation) (Type or print)
Type of water? depth of strata	Address 103 F St. Menistro 00
	a. W. Hell
Method of sealing strata off  Was well gravel packed? Leves □ No Size of gravel: 3/1/4 // // // // // // // // // // // // /	[Signed] (Water Well Contractor)
	1
Gravel placed from ft. to ft.	Contractor's License No Date, 19