

NOTICE TO WATER WELL CONTRACTOR: The original and first copy of this report are to be filed with the

RECEIVED

WATER WELL REPORT

MARK 950

WATER RESOURCES DEPARTMENT SALEM, OREGON 97310 within 30 days from date of well completion.

OCT 24 1978

STATE OF OREGON WATER RESOURCES DEPT. SALEM, OREGON (Do not write above this line)

State Well No. 4N/27E-28aa State Permit No.

(1) OWNER:

Name Jeddie Aglitt Address RT 1 Box 1808 Hermiston Oregon 97838

(2) TYPE OF WORK (check):

New Well [x] Deepening [] Reconditioning [] Abandon [] If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [x] Cable [] Dug [] Driven [] Jetted [] Bored []

(4) PROPOSED USE (check):

Domestic [x] Industrial [] Municipal [] Irrigation [] Test Well [] Other []

CASING INSTALLED:

6" Diam. from 0 ft. to 100 ft. Gage 250 Threaded [] Welded [x]

PERFORATIONS:

Perforated? [] Yes [x] No. Type of perforator used Size of perforations in. by in. perforations from ft. to ft.

(7) SCREENS:

Well screen installed? [] Yes [x] No Manufacturer's Name Type Model No. Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level Was a pump test made? [] Yes [x] No If yes, by whom? Yield: gal./min. with ft. drawdown after hrs. Bailor test 60 gal./min. with 2.3 ft. drawdown after 1 hrs. Artesian flow g.p.m. Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Cement & bentonite Well sealed from land surface to 20 ft. Diameter of well bore to bottom of seal 10 in. Diameter of well bore below seal 6 in. Number of sacks of cement used in well seal 4 1/2 bentonite sacks How was cement grout placed? Was a drive shoe used? [x] Yes [] No Plugs Size: location ft. Did any strata contain unusable water? [] Yes [x] No Type of water? depth of strata Method of sealing strata off Was well gravel packed? [] Yes [x] No Size of gravel: Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Morrow Driller's well number NE 1/4 NE 1/4 Section 28 T. 4N. R. 27E. W.M. Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 76 ft. Static level 72 ft. below land surface. Date 9-26-78 Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing Depth drilled 100 ft. Depth of completed well 100 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with columns: MATERIAL, From, To, SWL. Rows include Topsoil, Sand & gravel, Gravel.

Work started 9-25 1978 Completed 9-26 1978 Date well drilling machine moved off of well 9-26 1978

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief. [Signed] Donald Deane Date 9-26 1978 Drilling Machine Operator's License No. 1210

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Name TROY GRIFFIN (Person, firm or corporation) (Type or print) Address 900 HERMISTON AVE, HERMISTON ORE [Signed] Troy Griffin (Water Well Contractor) Contractor's License No. 65 Date 9-26 1978