

NOTICE TO WATER WELL CONTRACTOR: The original and first copy of this report are to be filed with the

RECEIVED NC NOV 4 - 1971 WATER WELL REPORT

STATE ENGINEER, SALEM, OREGON (Do not write above this line)

24A 4N/27-28 #2 G3408 State Well No. #2 G3408 State Permit No. 3397 Braat # 2 (assigned) MORE 984

(1) OWNER: Name Hansell Brothers, Inc. Address Rt. Box 173 Heyston, Or. 97838

(10) LOCATION OF WELL: County Morrow Driller's well number SW 1/4 SE 1/4 Section 28 T.4N R. 27E W.M. Bearing and distance from section or subdivision corner

(2) TYPE OF WORK (check): New Well [] Deepening [x] Reconditioning [] Abandon [] If abandonment, describe material and procedure in Item 12.

(11) WATER LEVEL: Completed well. Depth at which water was first found SEE PREVIOUS REPORT ft. Static level 67 ft. below land surface. Date 10/13/71 Artesian pressure lbs. per square inch. Date

(3) TYPE OF WELL: Rotary [] Driven [] Cable [x] Jetted [] Dug [] Bored [] (4) PROPOSED USE (check): Domestic [] Industrial [] Municipal [] Irrigation [x] Test Well [] Other []

(12) WELL LOG: Diameter of well below casing Depth drilled 127 ft. Depth of completed well 127 ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

(6) CASING INSTALLED: 16" Diam. from 1.00 ft. to 127 ft. Gage 375

Table with 4 columns: MATERIAL, From, To, SWL. Rows include: SEE PREVIOUS REPORT, GRAVEL, CHALK-GRAVEL, CEMENTED GRAVEL.

PERFORATIONS: Type of perforator used Mihhs Size of perforations 1/4 in. by 4 in. 1.00 perforations from 1.06 ft. to 8.6 ft.

(7) SCREENS: Well screen installed? [] Yes [x] No Manufacturer's Name Type Model No. Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level Was a pump test made? [x] Yes [] No If yes, by whom? FARMORE Yield: 3000 gal./min. with 58 ft. drawdown after 4 hrs.

Work started OCT. 2 1971 Completed OCT. 15 1971 Date well drilling machine moved off of well OCT. 15 1971

(9) CONSTRUCTION: Well seal—Material used SEE PREVIOUS REPORT Well sealed from land surface to Diameter of well bore to bottom of seal in. Diameter of well bore below seal in. Number of sacks of cement used in well seal sacks Number of sacks of bentonite used in well seal sacks Brand name of bentonite Number of pounds of bentonite per 100 gallons of water lbs./100 gals. Was a drive shoe used? [] Yes [] No Plugs Size: location ft. Did any strata contain unusable water? [] Yes [] No Type of water? depth of strata Method of sealing strata off Was well gravel packed? [] Yes [] No Size of gravel: Gravel placed from ft. to ft.

Drilling Machine Operator's Certification: This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief. [Signed] Charles Ferguson Date 11/2, 1971 (Drilling Machine Operator) Drilling Machine Operator's License No. 361

Water Well Contractor's Certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Name CHARLES JUNAMANN DRILLING CO. (Person, firm or corporation) (Type or print) Address 15 REAS AVE. W.W. WASH. [Signed] Charles Ferguson (Water Well Contractor) Contractor's License No. 230 Date 11/2, 1971