

RECEIVED

MORROW 961

4u/27E-306

STATE OF OREGON WATER WELL REPORT

NOV 12 1985

(as required by ORS 537.765) WATER RESOURCES DEPARTMENT PLEASE TYPE or PRINT IN INK

(for official use only)

(1) OWNER:

Name STARR - WOOD FERMS Address PO 951 City UMATILLA State

(2) TYPE OF WORK (check):

New Well [X] Deepening [] Reconditioning [] Abandon []

(3) TYPE OF WELL:

Rotary Air [X] Driven [] Rotary Mud [] Dug [] Bored []

(4) PROPOSED USE (check):

Domestic [] Industrial [] Municipal [] Thermal: [] Irrigation [X] Withdrawal [] Rejection [] Other: [] Piezometric [] Grounding [] Test []

(5) CASING INSTALLED:

Steel [X] Plastic [] Threaded [] Welded [] 18" Diam. from 1 ft. to 18 ft. Gauge .250 16" Diam. from 1 ft. to 42 ft. Gauge .250

LINER INSTALLED:

Steel [] Plastic [] Threaded [] Welded []

(6) PERFORATIONS:

Perforated? [] Yes [] No [] Size of perforations in. by in. perforations from ft. to ft.

(7) SCREENS:

Well screen installed? [X] Yes [] No Manufacturer's Name JOHNSON Type WIRE H/CRP Model No. Diam. 16" PS Slot Size .1060 Set from 42 ft. to 92 ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level Was a pump test made? [X] Yes [] No If yes, by whom? LAYNO 100 gal./min. with 20 ft. drawdown after 1 hrs.

(9) CONSTRUCTION:

Special standards: Yes [] No [X] Well seal—Material used PORTLAND CEMENT Well sealed from land surface to 18 ft. Diameter of well bore to bottom of seal 22 in. Diameter of well bore below seal 17 1/2 in. Amount of sealing material 8 SACKS sacks [] pounds [] How was cement grout placed? TRENCH

Was pump installed? NO Type HP Depth ft. Was a drive shoe used? [] Yes [X] No Plugs Size: location ft. Did any strata contain unusable water? [] Yes [] No Type of Water? depth of strata Method of sealing strata off Was well gravel packed? [] Yes [X] No Size of gravel: Gravel placed from ft. to ft.

(10) LOCATION OF WELL by legal description:

County MORROW NE 1/4 SW 1/4 of Section 30 Township 4N Range 27E WM. Tax Lot Lot Block Subdivision MAILING ADDRESS OF WELL (or nearest address)

(11) WATER LEVEL of COMPLETED WELL:

Depth at which water was first found 47 ft. Static level 47 ft. below land surface. Date 9-25-85 Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 8 ft. Depth drilled 92 ft. Depth of completed well 92 ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with columns: MATERIAL, From, To, SWL. Row 1: SAND, 0, 87. Row 2: Basalt, BLACK, BROKEN, 87, 92.

Date work started 9-18-85 /completed 9-25-85 Date well drilling machine moved off of well 9-25 1985

(unbonded) Water Well Constructor Certification (if applicable): This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief. [Signed] Jay Burd Date 9-25, 1985

(bonded) Water Well Constructor Certification: Bond Issued by: On behalf of LARRY BURD WELL DRILLING INC (type or print name of Water Well Constructor) This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief: (Signed) Jay Burd (Water Well Constructor) (Dated) 9-25-85

NOTICE TO WATER WELL CONSTRUCTOR The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

SP*46866-690