State Permit No.

NOTICE TO WATER WELL CONTRACTOR

The original and first copy DEC 2 2 1965 WATER WELL REPO
filed with the State Engineer, SALEM, OREGON 97510 ENGINEESTATE OF OREGON
within 30 days from the date LEM OREGON
of well completion.

(1) OWNER:	(11) WELL TESTS: Drawdown is amount water level is lowered below static level
Name ALL SAINTS CHURCH	Was a pump test made? Yes \(\) No If yes, by whom? STRASSE
Address 3847 N.E. GUSAN ST.	Yield: 400 gal./min. with 15 ft. drawdown after 8 hrs.
PORTIAND ORE.	<u>" 300 " 10 " 1 "</u>
(2) LOCATION OF WELL:	<u>" 200 " 6 " / "</u>
in all and	Bailer test gal./min. with ft. drawdown after hrs
County MULT. Driller's well number	Artesian flow g.p.m. Date
3E4NE 4 Section 36 T. / R. / E W.M.	Temperature of water 52 Was a chemical analysis made? Yes 🗆 No
Bearing and distance from section or subdivision corner	(12) WELL LOG: Diameter of well below casing
	Depth drilled 3.30 ft. Depth of completed well 3.30 ft
	Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation
a) myph on work (1 1) (4 b	MATERIAL FROM TO
(3) TYPE OF WORK (check): PRODUCTION WELL	BROWN CLAY AND SAND O 69
Vell Deepening □ Reconditioning □ Abandon □	PROWN SAND 70 80
If abandonment, describe material and procedure in Item 12.	BROWN SAND AND CLAY 80 146
PROPOSED USE (check): (5) TYPE OF WELL:	SAND AND GRAVEL 146 174
Potony Cl. Divron C	SAND AND GRAVEL BINDER 174 182
Domestic industrial municipal Cable Cable Jeffed	LOOSE JAND AND GRAVEL 182 195
rrigation Test Well Other Dug Bored	SAND AND GRAVEL 195 222
(6) CASING INSTALLED: Threaded Welded	BROWN CLAY LARGE GRAVE 122 23
10." Diam. from 0 ft. to 230 ft. Gage 279	
"Diam from ft. to ft. to ft. Gage ft. Gage ft. to ft. Gage ft. to ft. Gage ft. to ft. Gage ft	
"Diam. fromft. toft. Gage	
	-
(7) PERFORATIONS: Perforated? Yes No	
Type of perforator used 574R	
Size of perforations 3/4 in. by //4 in.	
280 perforations from	
ft. to ft.	
perforations from ft. to ft.	
perforations from ft. to ft.	
perforations from ft. to ft.	
8) SCREENS: Well screen installed? [] Yes No	
Walled Andrews Company	
Manufacturer's Name	
Model No.	
piam Slot size Set from ft. to ft.	Work started OCT 1719 6 5 Completed DEC 7 19 6
Diam. Slot size Set from ft. to ft. to ft.	Date well drilling machine moved off of well DEC 2 19 6
(9) CONSTRUCTION:	(13) PUMP:
Well seal—Material used in seal CEMENT	
, <i>G</i>	Manufacturer's Name
Depth of sealft. Was a packer used?	Type: H.P.
Diameter of well bore to bottom of sealin,	Water Well Contractor's Certification:
Were any loose strata cemented off? Tyes XNo Depth	
Was a drive shoe used? Yes No	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was well gravel packed? Yes No Size of gravel:	
Gravel placed from ft. to ft.	NAME KISTRASSER DRILLING GO (Person, firm or corporation) (Type or print) Address 8/10 SE SUNSET LANE FORTHAND O
Did any strata contain unusable water? Yes No	Register, firm of corporation) (Type or print)
Type of water? depth of strata	Address VIII - J - JUI - J - J - J - J - J - J - J - J - J -
Method of sealing strata off	Drilling Machine Operator's License No. 57
(10) WATER LEVELS:	PILOT
	[Signed] Woben of Masser
Static level /62 ft. below land surface Date ///6/65	(Water Well Contractor)
Artesian pressure lbs. per square inch Date	Contractor's License No. 10 Date DEC 14 1960