WATER WELL REPORT STATE OF OREGON

MULT

RECEIVED

_APR 16 1982

State Well No. 1h/2E-14dd

WATER RESOURCES DEPT

State Permit No.

	MLEM, OREGON	
(1) OWNER:	(10) LOCATION OF WELL:	
Name CITY OF PORTLAND	County MULT. Driller's well number	5588
Address 1220 SW STADE	SE 4 SE 4 Section 14 T. /N R. 21	W.M.
City PORTLAND State ORE 97264	Tax Lot # Lot Blk Subs	division
(2) TYPE OF WORK (check): WELL NO. //	Address at well location:	
New Well Deepening □ Reconditioning □ Abandon □	(11) WIA (DENT) T TAYLOT O	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	ft.
Rotary Air Driven Domestic Industrial Municipal	Static level ft. below land surface.	11 12
Rotary Mud Dug	Artesian pressure 2 lbs. per square inc	h. Date 4/3/8
Bored Thermal: Withdrawal Reinjection	(12) WELL LOG: Diameter of well below casing	The same of the sa
(5) CASING INSTALLED: Steel X Plastic	Depth drilled 583 ft. Depth of completed w	
Threaded U Welded	Formation: Describe color, texture, grain size and structure of mathickness and nature of each stratum and aquifer penetrated, with	aterials; and show at least one entry
24. "Diam. from	for each change of formation. Report each change in position of S	
	and indicate principal water-bearing strata.	
ENER INSTALLED 495 365	MATERIAL From	To SWL
10" Diam. from 3.7.5 ft. to \$5.5 ft. Gauge 3.6.5	SEE ATTACHED SHE	ET
5) PERFORATIONS: Perforated? Yes You		
Type of perforator used		
Size of perforations in. by in.		
perforations from ft. to ft.		
perforations from		
perforations from ft. to ft. to ft.		
(7) SCREENS: Well screen installed? Yes D No		
Manufacturer's Name UOP Joitison		
Type STAINLESS STEEL Model No.		
Diam/Slot Size25_Set from		
Diam. Slot Size Set from ft. to ft.		
Drowdown is amount water level is levened		
(8) WELL TESTS: below static level below static level		
Was a pump test made? Yes \(\sigma \) No If yes, by whom? \(\sigma \) TRASSER		
l: 2550 gal./min. with 178 ft. drawdown after 24 hrs.		
" " "		
Air test gal./min. with drill stem at ft. hrs.		
Bailer test gal./min. with ft. drawdown after hrs.		
Artesian flow 150 g.p.m.		
perature of water Depth artesian flow encountered 4.90. ft.	Work started DEC 3 19 81 Completed AF	PE Z 1982
(9) CONSTRUCTION: Special standards: Yes □ No 🗶	Date well drilling machine moved off of well ADP	7 1982
Well seal—Material used CEHENT GROUT	Drilling Machine Operator's Certification:	
Well sealed from land surface toft.	This well was constructed under my direct supervision	ı. Materials used
Diameter of well bore to bottom of seal	and information reported above are true to my best knowledge and belief.	
Diameter of well bore below seal	[Signed] Date (Drilling Mannine Operator)	4/13/198 4
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No.	
How was cement grout placed? LUMP THE GTROUT.	•	
THROUGH ONE INCH PIPE TROM	Water Well Contractor's Certification:	
DOTTOM UP AS CHSING WHS REMOVED	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.	
Was pump installed?	Name RUSTRASSER DRILLING CO	
Was a drive shoe used? X Yes \subseteq No Plugs Size: location ft. Did any strata contain unusable water? \subseteq Yes X No	(Person, firm or corporation)	(Type or print)
Type of Water? depth of strata	Address 8110 JE JUNSET LAWE TORT	ZHNO, ORE
Method of sealing strata off	[Signed] Louly I Th asso	•••••
Was well gravel packed? XYes □ No Size of 16-30.	(Water Well Contractor)	15 89
Grovel placed from 441 ft to 505 ft	Contractor's License No. Date Date	<u> </u>

Phone: 771-2355

R. J. Strasser Drilling Co.

8110 S. E. Sunset Lane Portland, Oregon 97206 April 14, 1982 RECEIVED

APR 16 1982

WATER RESOURCES DEPT SALEM. OREGON

Production well #11

clay and silt	0 - 41
silt, gravel and boulders	41 - 70
cemented gravel	70 - 112
brown and grey clay and gravel	112 - 138
gravel and clay	138 - 164
silty grey clay	164 - 186
green clay and gravel	186 - 193
sticky brown and green clay	193 - 2
green clay	200 - 220
grey clay and sand	220 - 237
sticky grey clay	237 - 243
green_sandy clay	243 - 278
grey and green clay	278 - 287
sand, gravel, and clay	287 - 323
sandstone	323 - 347
cemented gravel	347 - 373
cemented gravel, water seams	373 - 382
cemented gravel, clay seams	382 - 396
sand, gravel and clay	396 - 402
green and grey clay	402 - 418
grey clay	418 - 427
green clay, some gravel	427 - 453
brown clay	453 - 466
green clay	466 - 485
sand, gravel, and silt	485 - 513
loose gravel	513 - 520
sand and small gravel	520 - 532
silt, sand and gravel	532 - 573
grey clay	573 - 580
green clay	58 0 - 585

Phone: 771-2355

14/2E-14/8d

R. J. Strasser Drilling Co.

8110 S. E. Sunset Lane Portland, Oregon 97206

April 27, 1982

RECLUED

APR 29 1982

WATER RESOURCES DEPT SALEM, OREGON

City of Portland addendum to production well #11

(9) Construction

well sealed with cement grout from 170 to 190 feet well sealed with cement grout from 465 to 485 feet