WATER WELL REPORT STATE OF OREGON

MULT 1184

RECETED

State Well No. /M/2E-24ac

JUN 3 0 1982

WATER RESOURCES DEPT

State Permit No.	***************************************
Ω	1.1
Kecon	dition ina

	ALEM OREGON IZCOTOCOLON WO
(1) OWNER:	(10) LOCATION OF WELL:
Name CITY OF PORTLAND	County MULT: Driller's well number
Address 1220 SW 5TH AVE	\$41. 1/= 20/
City PORTLAND State CRE 9720	
(2) TYPE OF WORK (check): WELL NO Z	Address at well location:
New Well □ Deepening □ Reconditioning ♥ Abandon □	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found ft.
	Static level ft. below land surface. Date
Rotary Mud Dug Irrigation Test Well Other	Artesian pressure 4.5 lbs. per square inch. Date 6/21/8
Bored Thermal: Withdrawal Reinjection	(12) WELL LOG: Diameter of well below casing
(5) CASING INSTALLED: Steel Y Plastic Y	Depth drilled ft. Depth of completed well ft.
Threaded \square Welded	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry
"Diam from ft. to ft. Gauge	for each change of formation. Report each change in position of Static Water Level
"Diam. from	and indicate principal water-bearing strata.
LINER INSTALLED: SEE ATTACHED SHEET	MATERIAL From To SWL
" Diam. from	
Perforated? Yes No Type of perforator used	
Size of perforations in. by in.	
perforations fromft. toft.	
perforations from	
perforations from ft. to ft.	
(7) SCREENS: Well screen installed? ☐ Yes ☐ No	
Manufacturer's Name	
Type Model No.	
Diam. Slot Size Set from ft. to ft.	
Diam. Slot Size Set from ft. to ft.	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
s a pump test made? Yes 🗆 No If yes, by whom? STRASSER	
d: 3000 gal./min. with./28.5ft, drawdown after 24 hrs.	
" " " " "	
Mir test gal./min. with drill stem at ft. hrs.	
Bailer test gal./min. with ft. drawdown after hrs.	
	Work started MAY 10 1982 Completed JUNE 3/1982
9) CONSTRUCTION: Special standards: Yes \(\text{No} \)	Date well drilling machine moved off of well JUNE 24 19 82
Well seal—Material used	Drilling Machine Operator's Certification:
Well sealed from land surface to	This well was constructed under my direct supervision. Materials used
Diameter of well bore to bottom of sealin. Diameter of well bore below sealin.	and information reported above are true to my best knowledge and belief. [Signed]
Number of sacks of cement used in well sealsacks	[Signed] (Drilling Machine Operator) Date 63919/82
How was cement grout placed?	Drilling Machine Operator's License No5.7
	Water Well Contractor's Certification:
	This well was drilled under my jurisdiction and this report is true to
Was pump installed? Type HP Depth ft.	the best of my knowledge and belief
Was a drive shoe used? ☐ Yes ☐ No Plugs Size: locationft.	Name R. J. T. A. S. S. E. L. L. L. L. C. (Type or print) (Person, firm or corporation) (Type or print)
Did any strata contain unusable water? Yes No	Address 81105E SUNSET LANE PORTLAND ORE
Type of Water? depth of strata	15: mail Robert I The 1 The
Method of sealing strata off	[Signed] (Water Well Contractor)
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	Contractor's License No. 10 Date JUNE 29, 1982
Gravel placed from ft. to ft.	,

Mult. Ca 11/28-24ac RECETED 20-City of Portland WATER RESOURCES DEPT

No BALEM, OREGON

(5) LINER INSTALLED

SINCH STAINLESS STEEL PIPE , 180 WALL THICKNESS FROM 376.5 TO 413.5 FT. WITH A INCH THICK RUBBER PACKER 12 IN. LONG AT 377 AND A FINCH THICK RUBBER PACKER 18 INCHES LONG AT 411 FF.

PORTLAND WELL

SINCH P.V.C. PIPE 322 WALL THICKNESS FROM 413.5 TO 453.5 FEET WITH I INCH THICK RUBBER PACKERS 18 INCHES LONG AT 415.5, 431, AND 451 FEET