## PECEIVED JAN 25 1962 WATER WELL REPORT

File Original and First Copy with the STATE ENGINEER, SALEM, OREGON

STATE ENGINEER STATE OF OREGON

**G-**1882 State Permit No.

(1) OWNER:	(11) WELL TESTS: Drawdown is amount water level is lowered below static level	S
Name Fred Meyer, Inc.	Was a pump test made? Yes \( \subseteq \) No If yes, by whom? -	
Address 721 S. W. 4th	gan, man, was a surface of the surfa	hrs.
Portland, Oregon	400 35 = 8	
(2) LOCATION OF WELL:	<del>- 500 42 ~ 8</del>	
County Owner's number, if any—	Bailer test gal./min. with ft. drawdown after  Artesian flow g.p.m. Date	hrs.
S.E. 14 N.W. 14 Section 32 T. 1N R. 2E W.M.	Temperature of water Was a chemical analysis made? ☐ Yes	□ No
Bearing and distance from section or subdivision corner 650 North and 1610 Westle from S.E.		
corner of N.W. 4 of Section 32.	(12) WELL LOG: Diameter of well12	inches.
Corner of N.W. 4 of Section 62.	Depth drilled 295 ft. Depth of completed well 295	ft.
	Formation: Describe by color, character, size of material and struct show thickness of aquifers and the kind and nature of the material stratum penetrated, with at least one entry for each change of for	ure, and in each
		rmation.
	MATERIAL FROM	то
TYPE OF WORK (check):	Sand and gravel with binder 50	139
New Well   Deepening □ Reconditioning □ Abandon □	- Daire Care Selection / Transport	160
If abandonment, describe material and procedure in Item 11.	Sand, gravel and boulders 160	168_
PROPOSED USE (check): (5) TYPE OF WELL:	Sand and gravel with binder 168	182
	Sand and gravel water bearing 182	210
mestic   Industrial   Municipal   Rotary   Driven   Cable   Jetted	Sand and gravel with binder 210	244
Irrigation   Test Well   Other   Dug   Bored	Mostly sand with scattered grave 1244	256
(6) CASING INSTALLED: Threaded □ Welded □	Sand and gravel with some water 256	273
	Tight sand and gravel 1273	285
"Diam. fromft. toft. Gage	Cemented_gravel285	295_
"Diam. from		<del></del>
Dian. Hour		
(7) PERFORATIONS: Perforated? ☼ Yes ☐ No		
Type of perforator used Star		
SIZE of perforations 12 in. by 3/8 in.		
660 perforations from 185 ft. to 200 ft.		
600perforations from265ft. to280ft.		
perforations from ft. to ft.		
perforations from		
perforations fromft. toft.		
SCREENS: Well screen installed		
Manufacturer's Name		
Type Model No.		
Slot size Set from ft. to ft.		
Slot size Set from ft. to ft.	Work started June 29 19 61. Completed Sept. 19	1861
		· · · · · · · · · · · · · · · · · · ·
(9) CONSTRUCTION:	(13) PUMP:	
Was well gravel packed? ☐ Yes ▼ No Size of gravel:	Manufacturer's Name	
Gravel placed fromft. toft.	Type: DEEP WELL TURBINE HP. 40	
Was a surface seal provided? Yes No To what depth?50 ft.	W. I. D. W Cd. Lamanda	
Material used in seal— cement  Did any strata contain unusable water? ☐ Yes ☐ No	Well Driller's Statement:  This well was drilled under my jurisdiction and this report is	
Type of water? Depth of strata	true to the best of my knowledge and belief.	
Method of sealing strata off		
AND THE PERSON OF THE PERSON O	NAME R.J. STRASSER DRILLING CO. (Person, firm, or corporation) (Type or print)	
(10) WATER LEVELS:	Address 8110 S. E. Sunset Lane, Portland 6	
Static level 150 ft. below land surface Date 9/15/61	AUULESS SILLS	
Artesian pressure lbs. per square inch Date	Driller's well number	
Log Accepted by:	(taul () (terlinan)	
Log Accepted by	[Signed] (Well Drill#)	
[Signed] Date Of the part of t	License No. 10 Date Oct. 3.	19 61
FREN. MENER IN	A TACOLOG 110.	