
FÉR WELL REPORT STATE OF OREGON



RECEIVED // OCT 27 1981

State Permit No.
WATER RESOURCES DEPT

SALEA, OREGON

(1) OWNER:	(10) LOCATION OF WELL:	
Name CITY OF TORTLAND	County MyloT. Driller's well number 5583	
Address 1220 S.W. STH AVE	SW 4 SW 4 Section 20 T. /N R. 3E W.M.	
City PORTLAND State ORE	Tax Lot # Lot Blk Subdivision	
(2) TYPE OF WORK (check): No 8	Address at well location:	
New Well Deepening □ Reconditioning □ Abandon □	(11) XXADDED I EXTEL. Completed and I	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found ft.	
	Static level ft. below land surface. Date Artesian pressure 4.3/1/. lbs. personarcioch. Date 9/2//8/	
Rotary Air	Artesian pressure 4,3/W, lbs. por equations. Date 9/2//8/ (12) WELL LOG: Diameter of well below casing	
(E) CACINIC INCTALLED.	Depth drilled 450 ft. Depth of completed well 448 ft.	
(5) CASING INSTALLED: Steel Threaded Plastic Welded	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry	
20. Diam from 10 ft to 330 ft Gauge 375	for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.	
DIMERING TO DE STAINLESS STEEL FIPM	MATERIAL From To SWL	
70 300 300		
/O."Diam. from	SEE ATTACHED SHEET	
(6) PERFORATIONS: Perforated? ☐ Yes X No	*	
Type of perforator used		
Size of perforations in. by in.		
perforations from ft. to ft.	,	
perforations from		
perforations from ft. to ft.		
(7) SCREENS: Well screen installed? Yes □ No		
Manufacturer's Name UOP JOHNSON		
Type STAINLESS STEELModelNo 413		
Diam. Slot Size Set from 7, 3 ft. to 420 ft.		
Diam		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		
wes a pump test made? Yes □ No If yes, by whom? JTRASSER		
d: 2500 gal/min. with 266 ft. drawdown after 72 hrs.		
Air test gal./min. with drill stem at ft. hrs.		
Bailer test gal./min. with ft. drawdown after hrs.		
Autesian flow S g.p.m.	N=	
perature of water Depth artesian flow encountered ft.	Work started MAY 619 8/ Completed SEPT 3819 8/	
(9) CONSTRUCTION: Special standards: Yes \(\sigma \) No \(\)	Date well drilling machine moved off of well SEPT 39 1981	
Well seal—Material used CEMENT GROUT	Drilling Machine Operator's Certification:	
Well sealed from land surface toft.	This well was constructed under my direct supervision. Materials used	
Diameter of well bore to bottom of seal	and information reported above are true to my best knowledge and belief.	
Diameter of well bore below seal 2.4 in.	[Signed]	
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No	
How was cement grout placed? HOUT WAS POMED		
THEOLEH DUE INCH PIPE	Water Well Contractor's Certification:	
HO THE SUIN THE WHO KENONED	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.	
Was pump installed?	Name R. J. STRASSER DRILLING CO	
Was a drive shoe used? Yes \(\sigma \) No Plugs	(Person firm or corporation) (Type or print)	
Type of Water? depth of strata	Address Of OSL SUNDER LAND UK	
Mathod of seeling strete off	[Signed] Kath LThass	
Was well gravel packed? Yes No Size of gravel: 03-028	(Water Well Contractor) Contractor's License No. / Date OCT 11, 19.8/	
Gravel placed from 310 ft. to 4.4.8 ft.	Commacus a License Iv	

R. J. Strasser Drilling Co.

8110 S. E. Sunset Lane Portland, Oregon 97206 October 21, 1981

#hone: 771-2355

RECEIVED

OCT 27 1981

WATER RESOURCES DEPT SALEM, OREGON

1413E-20cc

20 City of Potland

log of well #8

top soil	0 - 1
clay Xaz	1 - 10
sandy silt	10 - 41
Packed sand and silt	41 - 44
sand	44 - 56
sand and gravel	56 - 61
loose gravel	61 - 62
sand, gravel and clay	62 - 66
cemented gravel	66 – 83
grey clay and gravel	83 - 90
green, grey and brown clay	90 - 120
green, grey and brown cray green and grey clay	120 - 138
brown and green clay	138 - 144
clay with layers of sandstone	144 - 165
sandy clay	165 - 170
clay with layers of sandstone	170 - 191
slightly cemented sand	191 - 200
cemented sand and gravel	200 - 214
silt, sand and gravel	214 - 240
loose sand and gravel	240 - 245
slightly cemented sand and gravel	245 - 270
loose gravel	270 - 274
sticky clay and gravel	274 - 290
clay	290 - 333
sand, gravel and sandstone seams	333 - 342
sand and gravel	342 - 370
compacted sand and gravel	$370 - \overline{3}80$
silty sand and gravel	380 - 393
sand and gravel	393 - 430
sand, gravel and sandstone seams	430 - 433
black sand and gravel	433 - 438
black sand	438 - 446
silt	446 - 450
DALL	

Phone: 771-2355

1 W3E-200C

R. J. Strasser Drilling Co.

8110 S. E. Sunset Lane Portland, Oregon 97206

April 27, 1982

RECLIED

APR 29 1982

WATER RESOURCES DEPT BALEM, OREGON

City of Portland
addendum to production well #8

(9) Construction

well sealed with cement grout from 100 to 120 feet well sealed with cement grout from 310 to 330 feet